

CYBER SERIES

Biometric

Cyber SERIES



The Biometric Cyber Series is a time and data collection terminal that sets a new standard in the industry by incorporating your choice of two proven finger scan technologies: E-field or capacitive sensor. The Cyber Series is able to provide security that will save your company money through the elimination of buddy-punching and time theft. Enjoy all the benefits of Biometric technology in the Cyber Series without having to break the bank.

- Single or multi-clock environment
- Up to 1MB of RAM
- Up to 512KB Flash
- EIA Standard RS232 or RS485 compatible
- 10/100BASE-T Ethernet
- Fingerprint E-field or capacitive sensor technology
- On-board setup and diagnostics utility
- Digital bar code wand port
- Expansion slot for support of plug-in options
- External proximity reader support

Answers for HR Professionals™



To learn more about ATS and the Cyber Series, visit www.accu-time.com or call 860-870-5000.



Specifications

- DISPLAY** 4 line x 20 character super twist LCD
- CLOCK** 12 or 24 hour format, USA or international (quartz precision)
Time stamp of data transactions
- KEYPAD** Software-defined function keys
Large 20-key tactile 4x5 matrix
Custom user-defined keypad legends
- MEMORY** Up to 1MB RAM available
Up to 512k flash memory
- PROGRAMMING** ATS Universal Command Set, C programming language, or third-party custom application packages
- SELF-TEST** On-board setup and full-feature diagnostics
- INTERFACE** 802.3 10/100BASE-T Ethernet (optional)
EIA Standard RS232 or RS485
Internal modem (optional)
Optional DI/DO or serial interface printer port
- ENCLOSURE** Die cast aluminum housing with key-lockable base
- POWER** +10 to +17VDC (12 nominal)
Optional non-interruptible power source with charger
- ENVIRONMENT** Operation: 32° to 110°F (0° to 43°C)
- PHYSICAL** Size: 7.25" x 10" x 4" (18.4cm x 25.4cm x 10.2cm)
Weight: 2.45 lbs. (2.2 kg.)
- CERTIFICATIONS** CE Mark, FCC Part 15 and Part 68
- ACCESSORIES**
- Integrated visible or infrared bar code slot readers
 - Integrated magnetic slot readers
 - Solid state or dry contact relay modules
 - Integrated or external proximity readers
 - Serial interface printer port

Cyber Series Biometric Configuration Guide

Terminal Type	Display	Ethernet		Modem	Memory	Flash	Mounting	Prox.	DI/DO	1 to 1 w/pin	1 to X no pin
		10M	10/100M								
CSSB	4x20	---	---	Opt.	128K	256K	Gull	---	---	Std.	Opt.
CSEB	4x20	Std.	---	---	128K	256K	Gull	---	---	Std.	Opt.
CS1B	4x20	---	---	Opt.	512K	256K	Lock	Opt.	Opt.	Std.	Opt.
CS2B	4x20	---	Std.	Opt.	512K	256K	Lock	Opt.	Opt.	Std.	Opt.
CS3B	4x20	---	Std.	Opt.	1MB	512K	Lock	Opt.	Opt.	Std.	Opt.

Accu-Time Systems, Inc.

One Accu-Time Plaza
Route 83
Ellington, CT 06029

1-800-355-4648

www.accu-time.com

TEL: (860) 870-5000

FAX: (860) 872-1511

EMAIL: sales@accu-time.com

Accu-Tech Systems Ltd

31 Venture Wales
Bedwas House
Business Park
Caerphilly
South Wales
United Kingdom
CF83 8DW

+44 (0) 2920 885599

www.accu-tech.co.uk

SERIES
Biometric

Connecticut • Chicago • Sarasota • Boston • United Kingdom