

# ARGOX CAN.



**A-150**

## A-150

The A-150 thermal transfer printer is easy to operate, space-saving, and offers optimal performance at a competitive cost. A new generation mechanism with centralized printing alignment allows drop-in reloading of 5-inch OD media rolls 1- to 4-inches wide for use in many types of applications. A see-through window lets you monitor media supply. The A-150's options include a cutter and dispenser kit, real time clock card, print server, and 2MB Asian font card.



**A-200**

## A-200

The A-200 is a sturdy, compact thermal transfer printer that features a 32-bit microprocessor and 2MB DRAM for printing performance up to four inches per second. A bi-directional USB interface is fast and flexible, which is in addition to standard parallel and serial interfaces. The centralized printing alignment allows 5-inch OD media rolls and the see-through window and reflective sensors make it easy to manage a range of media applications. The A-200's enhanced printing capabilities and ease-of-use offers an exceptional entry-level printer.

Specifications	A-150	A-200
Printing Method	Thermal Transfer	
Printing Resolution	203dpi (8 dots/mm)	203dpi (8 dots/mm)
Printing Speed	2 ~ 4 ips (51~ 102 mm/s)	2 ~ 4 ips (51~ 102 mm/s)
Printing Length	Max 8" (203 mm)	Max 45" (1143 mm)
Printing Width	Max 4.1" (104 mm)	Max 4.1" (104 mm)
Memory	512KB DRAM 512KB Flash ROM	2MB DRAM 2MB Flash ROM
CPU Type	16bit RISC microprocessor	32bit RISC microprocessor
Media Sensor	Reflective	Reflective / See- through
Display	LED indicator x 2	LED indicator x 2
Operation Interface	Button x 1	Button x 1
Communication Interface	Centronics parallel RS-232 serial	Centronics parallel RS-232 serial Bi-USB (Full Speed)
Fonts	Int'l character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23"H (1.25mm ~ 6.0mm) All fonts are expandable up to 24 x 24 4 direction 0° ~ 270° rotation Soft fonts are downloadable	
Barcodes	Code 39, Extended Code 39, Code 93, Code 128 UCC Code 128 (Subset A, B, C) Codabar, Interleave 2 of 5, EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A, E 2&5 add on, POSTNET, German POST, Matrix 25, Maxicode, PDF-417, Data Matrix	
Graphics	PCX bit map, GDI graphics	
Software	Argox PPLB Language Windows Driver (Win 98/2000/NT/XP) Label editing software - BarTender / Printer Utility	
Media	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper and fabric label Max width 4.25" (108mm) Min width 1.0" (25.4 mm) Thickness 0.0025" ~ 0.01" (0.0635mm ~ 0.254mm) Max roll capacity 5" (127mm) OD Core size 1" (25mm) ID	
Ribbon	Wax, Wax/Resin, Resin (Outside coating ribbon) Ribbon width - 2", 4" Ribbon roll - max OD 1.5" (38mm) Ribbon length - max 3937"(100 M) Core size - ID 0.5" core (13mm) with notch	
Mechanism Request	Build-in Tear off bar, front-open cover, clear window, fan fold paper back cover, same mechanism structure, face-out ribbon run way, face-in media run way, un-adjustable TPH carrier	
Dimensions	W200 x H170 x L245 mm, 4.8 lbs (2.2 kgs)	
Power Source	110/220 VAC ±10%, 50/60 Hz, external power adapter	
Agency Listing	CE, UL, CUL, FCC Class A, CCC	
Operation Environment	40° F ~ 100° F (4° C ~ 38° C) ; 10 ~ 90% non-condensing	
Optional Items	Cutter, Dispenser kit, Real time clock card, ArgoKee, 2MB Asian Font card (Traditional Chinese, Simplified Chinese, Korean and Japanese)	

Specifications subject to change without notice

