



ToughRunners

Performing under all Conditions !



- CMOS, Laser and Laser Long Range scan engines available
- Ergonomic torch-shaped design for accurate barcode aiming
- Bluetooth Class 1 (up to 100 m)
- Perfectly suitable for industrial environments : IP54 and it resists to multiple drops onto concrete
- Comprehensive scanning indicators : LED, beeper and vibrator
- Battery autonomy : over 15,000 scans
- Xtreme version IP65 available

- Goods in - Goods out
- Stock Management
- Inventory Management

ToughRunners Specifications

STANDARDS

Bluetooth 2.0

SUPPORTED INTERFACES

Plug & Scan RS232, Plug & Scan USB Standard Dongle

RADIO RANGE

Class 1 : up to 330 ft (100 meters)

USER INTERFACE

Buzzer 80 dB(A)
LED Tricolour (Red, Green, Blue)
Vibrator yes

USING MODES

Real time
No Data Loss Mode with buffer:
up to 100 UPC codes

READING MODES

Switch
Laser Beam ON via Bluetooth
Autoscan ("No Duplicate Scan" mode option)

PHYSICAL

Length 192 mm
Width 56 mm
Height 49 mm
Weight 6 oz (170 g)

ENVIRONMENT

Operating temperature 0°F - +122°F (0°C - +50°C*)
Storage temperature +14°F - +140°F (-10°C- +60°C)
Humidity 15 - 95%
Shock 10 drops onto concrete (59 in / 1.50 meters)
Sealing IP54 (IP65 for Xtreme version)
Electrostatic discharge 8 kV air discharge and 4 kV of contact discharge

* Available in Xtreme version (-22°F / -30C°)

ENERGY

Battery Li-ion
Capacity 720 mAh
Charging time 4h for a full charge
Battery autonomy over 15,000 scans (10 scan/min)

CRADDLE

Power supply 4.5V - 5.5 Volts
Voltage 260 mA to 5V

REGULATOR

CE, FCC part 15, Bluetooth

Content

- 1 ToughRunners scanner
- 1 Charger
- 1 CD of software documentation

DECODING CAPACITIES


Supported symbologies Code 2 of 5 (standard and interleaved)
ATA Code 2 of 5, Codabar/ Monarch, Code 128
UCC / EAN 128, Code 39, Code 93, UPC-A, UPC-E
EAN 8/EAN 13, JAN 8/JAN13, ISBN, MSI, PLessey
GS1-128 (UCC/EAN-128)

SCAN ENGINE


	BTR-L	BTR-LA	BTR-LR
Reference	EV15 (Intermec)	SE1200HP (Motorola)	SE1200LR (Motorola)
Reading technology	CMOS	Laser	Laser
Reading Distance	4 to 31 in 10 to 80 cm	4 to 55 in 10 to 140 cm	10 to 90 in 25 to 230 cm
Scan rate	200 scans/ sec	35 scans/ sec	35 scans/ sec
Scan angle	40°	42°	30°

LIGHT


0 to 100,000 lux 4,844 to 86,112 lux 4,844 to 86,112 lux



BTR-L



BTR-LR



BTR-LA

Available accessory



Charging Cradle