

Code Reader 2.0™



Features & Benefits

- Lightweight, ergonomic, fully-mobile modular design (hand held, handle, presentation stand)
- User feedback with vibration and/or audible tones
- Equally efficient in batch, cabled or wireless modes
- Reads all linear stacked and 2D matrix symbologies
- Data output via Bluetooth, USB , RS232 or Keyboard options
- Powerful data management capability via JavaScript
- Firmware is field upgradeable
- Accessories available to further ruggedize reader for high-volume use scenarios



Overview

The Code Reader 2.0 (CR2) can read and decode all existing bar code symbols. Whether you are reading smaller, high density two-dimensional codes, or larger, low density linear codes, the CR2 will outperform all other devices in its class. The CR2 incorporates a unique dual path optical system, a 1.3 million pixel CMOS sensor and a 400 MHz processor. The CR2 reader features a beep and vibrate mode, multifunction LED indicators and two top control buttons. While it can be further ruggedized for high-volume use case scenarios, the CR2 reader is lightweight with a unique ergonomic design. CR2 operates efficiently in batch, cabled or wireless modes with accessories to further enhance use-case functionality.

Wireless readers are available with a Bluetooth® Class I radio (with a range of 300 feet/ 100 meters) or Class II radio (30 feet/ 9.5 meters) with Bluetooth firmware V2.0; the firmware is easily upgradeable in the field. The CodeXML™ Bluetooth Modem enables simplified wireless transmission of captured data to a host computer or system. Code's JavaScript Software Development Kit provides programming tools for integrating captured data in enterprise software.

The CR2 can be accompanied by a variety of accessories, making it is the only product available in: batch, cabled or wireless formats; hand-held, ruggedized cabled, or battery handle use-case scenarios; and lanyard hook attachment or presentation stand form factors. Code's full line of reader accessories tailor the reader's use to best meet your needs.

Code Reader 2.0™ Specifications

Physical Characteristics

Reader Dimensions:	1.3" H x 4.3" L x 1.8" W (3.3cm H x 10.9cm L x 4.6cm W)
Reader Weight:	2.5 oz (71.5 g)
Battery Weight:	2.1 oz (59.5 g)
Battery Blank Weight:	0.5 oz (13.6 g)

Performance Characteristics

Field of View:	Near: 21.5° horizontal by 16.2° vertical Far: 22.9° horizontal by 11.6° vertical
Focal Point:	Near: approximately 4" Far: approximately 9"
Sensor:	CMOS 1.3 Megapixel (1024x1280) 256 level gray scale
Optical Resolution:	Near Field: 1024 x 640 Far Field: 1024 x 640
Pitch:	± 60° (from front to back)
Skew:	± 60° from plane parallel to symbol (side-to-side)
Rotational Tolerance:	± 180°
Print Contrast Res.:	25% (1-D symbologies) or 35% (PDF417) absolute dark/light reflectance differential, measured at 650 nm
Target Beam:	Class 2M Visible Laser Diode at 630nm
Ambient Light Immunity:	Sunlight: Up to 9,000ft-candles/96,890 lux
Shock:	Withstands multiple drops of 6 feet (1.8 Meters) to concrete
Power Requirements:	Reader @ 5vdc (mA) - Typical = 140; Peak = 310; Idle = n/a; Sleep = 3; Bluetooth Radio @ 90m away (mA) Typical = 280 Peak = 350; Idle = 96; Sleep = 3 1950 mAH Battery in reader with radio will support 11,000+ reads/transmits per charge.
Optional Cable Interfaces:	USB (Full Speed V1.1), RS232 & PS/2

Accessories

- Single-Bay or Two-Bay Battery Charger
- Cabled or Wireless Handles
- Battery Handle Charger or Universal Mountable Charger
- CodeXML™ Router Software
- CodeXML™ Bluetooth® Modems
- Software Development Kits
- Reader Stand
- Elastomer Boot
- USB, PS/2, or RS232 Cables
- 1950 and 3900 mAh Li-Ion Batteries
- Battery Blank
- US, Europe/South America, or UK Power Supply

User Environment

Operating Temperature:	0° to 50° C / 32° to 122° F
Storage Temperature:	-20° to 65° C / - 4° to 150° F
Humidity:	5% to 95% non-condensing
Decode Capability:	1D: UPC/EAN/JAN, Code 39, Code 128, Interleaved 2 of 5, Codabar, GS1 DataBar (RSS), MSI Plessey, Code 11, Code 93, NEC 2 of 5, Matrix 2 of 5, Trioptic Code, Telepen, Hong Kong 2 of 5, Pharmacode, Composite Codes Stacked 1D: PDF417, Micro PDF417, Codablock A & F 2D: Data Matrix, QR Code, Micro QR Code, Aztec Code, Maxicode Proprietary 2D: GoCode® (Requires Additional Licensing) Postal: USPS OneCode (4CB), POSTNET, PLANET, Japanese Post, Australian Post, Royal Mail, KIX Code OCR: OCR-A and OCR-B Fonts
Image Output Options:	Formats: JPEG, Raw (Uncompressed)
Field Selection:	Near or Far
Resolution Selection:	1024 x 640 (Multiple Window Options)
Time Stamp:	Interval Logging
Data Editing:	JavaScript (Additional License Required) / CodeXML™ Rules



Working Ranges

Code Reader 2.0 Performance	
Near Field	Depth of Field
6.3 mil Data Matrix	63 mm - 99 mm
20.8 mil Data Matrix	46 mm - 113 mm
5.8 mil PDF417	55 mm - 97 mm
7.5 mil Code39	78 mm - 108 mm
10.5 mil GS1 DataBar Stacked	38 mm - 108 mm
12.5 mil Code128	101 mm - 131 mm
Far Field	Depth of Field
6.3 mil Data Matrix	135 mm - 178 mm
20.8 mil Data Matrix	109 mm - 237 mm
7.5 mil Code39	114 mm - 245 mm
10.5 mil GS1 DataBar Stacked	89 mm - 276 mm
12.5 mil Code128	67 mm - 306 mm
<i>All samples were high quality codes and were read along a physical center line at a 10° angle. Default AGC settings were used. Accuracy= +/- 10%.</i>	

code

14940 S Pony Express Rd. #500
Bluffdale, UT 84065

phone: (801) 495-2200 fax: (801) 495-2202

web: www.codecorp.com

Specifications subject to change without notice.