



Portable Power

Code Courier direct thermal and thermal transfer portable printers deliver unsurpassed performance in a surprisingly compact package. With a full suite of on-board bar codes, including high density two dimensional codes, a rich text font selection, and 2.5 ips print speed, Courier printers have the power you need for the most demanding applications. The sophisticated battery management enables the Code Courier to print long after other portables stop.

Rugged Reliability

Code Courier's rugged design performs well in the most adverse environments. The high impact clamshell case and durable metal internal frame assure shock resistance even in demanding portable applications. Over the years, thousands of Code Courier printers have proven themselves in factories, loading docks, and on the road.

Direct thermal and thermal transfer models.



Wide-open media loading

Print	Technology	PW422003:	Direct Thermal
		PT422003:	Thermal/Direct Transfer
	Width (max)	4.16" / 106mm	
	Length (max @ 203 dpi)	6.0" / 152mm	
	Speed	2.5 ips / 63mm/sec	
	Resolution	Selectable 203 or 101 dpi	
Media	Width	2.4" - 4.25" / 61-108mm	
	Minimum Form Length	1.0" / 25mm	
	Media Roll Diameter	PW422003:	2.1" / 53mm
		PT422003:	1.9" / 48mm
	Ribbon Length	1000" / 25.5m (PT422003 only)	
	Label Indexing	Black bar or gap	
Bar Codes	Types Supported	UPCA/E/E1, Code 39, I2of5, EAN8/13, EAN128, Add 2, Add 5, Plessey, MSI MS1,128A/B/C, Codabar, MaxiCode, PDF417	
Fonts	Traditional Bitmapped	6 styles with up to 10 x10 magnification, variable boldness and spacing	
	Scalable Smooth Fonts	Three Ultra Font styles for smooth characters in any size and boldness	
	Rotation	90°, 180°, 270°	
Graphics	Features	Foreground and background bitmapped graphics, sizeable graphics windows	
Memory	SRAM	128K	
	FLASH	256K	
Communication		RJ45 RS232 Serial, IrDA (opt.) Up to 115kb	
Battery	Type	Rechargeable 14 V NC	
	Charging	Via external AC adapter (included)	
	Charge Time	3 to 4 hours in standard conditions	
	Battery Life	500 charge/discharge cycles, typical	
	Power Management	Sleep mode, timed power shutoff, auto speed control, low battery sensing temperature compensation	
	Labels per Charge	250 4" x 3" labels at 30% density in standard conditions, over 500 in many applications	
Environmental	Battery Model	41° F to 122° F	5° C to 50° C
	Forklift Model	-4° F to 122° F	-20° C to 50° C
	Storage	-13° F to 158° F	-25° C to 70° C
		0% to 85% non-condensing RH	
Dimensions	Height	PW422003:	2.75" / 70mm
		PT422003:	4" / 102mm
	Width	8.4" / 213mm	
	Depth	4.75" / 120mm	
Weight	With Battery and Media	PW422003:	3.0lb 1.36kg
		PT422003:	3.75lb 1.7kg
Options and Accessories	Supplied	Manual, battery, battery charger, shoulder strap, Windows® printer drivers	
	Optional	Carrying handle, communication cables, five bay battery charger, annual service contracts, forklift power adapters, forklift mount	
	Factory Options	Custom communication interfaces, label dispenser, fork lift capable, wireless IrDA interface	
Typical Printhead Life		2,000,000"	50,800m

Features and Benefits

Speed

With print speed up to 2.5 ips, Code Courier is the world's fastest 4.25 inch portable printer. Automatic speed control assures high quality printing with maximum throughput in adverse conditions.

Convenience

Code Courier is the world's smallest and lightest 4.25 inch thermal transfer portable printer. With battery and media, it weighs under four pounds and is not much larger than a paperback book.

Ease of Use

The Code Courier clamshell design makes media and battery loading fast and easy. Plus, the included Microsoft Windows® drivers make the Code Courier compatible with Windows® applications.



For additional information about Cognitive products, contact the addresses below or visit our web site at www.cognitive.com

USA

691 Corporate Circle
Golden, CO 80401
Tel: +1 303 273 1400
Toll free: +1 800 525 2785
Fax: +1 303 273 1414
sales@cognitive.com

Europe

Atlantic Street
Altrincham
Cheshire
WA14 5QJ UK
Tel: +44 161 929 9933
Fax: +44 161 927 7664
europesales@cognitive.com

Asia-Pacific

PO Box 726
Level 3, 39 Leighton Place
Hornsby NSW 2077 Australia
Tel: +61 2 9477 1999
Fax: +61 2 9477 1453
asiasales@cognitive.com

Japan

2-23-2 Higashi-Ikebukuro
Toshima-KU
Tokyo 170 Japan
Tel: +81 135 391 7689
Fax: +81 135 391 7692
japansales@cognitive.com