



IMAGETEAM™ 4710HD/HD10

Fixed Mount 2D Image Reader

The Hand Held Products IMAGETEAM™ (IT) 4710 Image Reader can be configured as either a hand held or fixed mount device that reads matrix, stacked linear and conventional linear bar codes, as well as a single line of OCR-A and OCR-B fonts. Multi-line OCR applications can also be read. The IT4710 has the power to capture and download images to a PC for applications that include signature capture, PC-based decoding, and image lift requirements.

The IT4710 Reader can be used in retail, transportation, packaging, printed circuit board manufacturing, electronic component manufacturing, and clinical/diagnostic applications that include test tube and reagent package labels.

The IT4710 can be configured for keyboard wedge, HHLC (Code 128 emulation), TTL, or True RS-232. The IT4710 connects to all popular PCs and portable data terminals. HHLC mode can be used with external wedge decoders and portable terminals or other devices without 2D decoding capability.

The IT4710 features integrated processing for a one-piece scanning solution -- no additional boxes or electronics needed. The reader provides omni-directional and auto-discrimination decoding for symbologies, such as MaxiCode, PDF417, QR, Data Matrix, Aztec code, RSS code, composite codes, postal codes, Code 39, Code 93, Interleaved 2 of 5, Codabar, Code 128, UPC, and EAN. Additional symbologies will be added based on market demand.

Because the IT4710 is a fixed focus device, four product models with different focal points are available. Two high density scanners are available: IT4710HD and IT4710HD10. The IT4710HD, with a focal point of 2 inches, is recommended when the matrix symbols are less than 10 mil. The IT4710HD10 is recommended for applications when the matrix codes are greater than 10 mil. This version, with a focal point of 3 inches, maximizes the depth of field on 10 mil matrix codes, which directly correlates to greater functionality by the end user. The long range (LR/LX) models of the IT4710 are highlighted in separate data sheets.

Features & Benefits

2D Image Reader

Hand held or fixed mount image reader for reading and decoding 2D symbologies, and capturing images.

Supports All Popular 2D Symbologies

Fixed mount IT4710 supports all popular matrix and stacked linear symbologies: MaxiCode, Aztec, Aztec Mesa, Data Matrix, PDF417, QR, and MicroPDF417.

Fixed Position Reader

Opens up new 2D bar code and image capture possibilities for fixed scanning applications.

Omni-Directional Scanning

The video technology offers omni-directional scanning, even on linear codes, greatly simplifying operator training and increasing productivity.

Aiming

The IT4710 has a bright, intuitive aiming line.

Autodiscriminates Between Supported Symbologies and Fonts

Reads all major linear, stacked linear, and matrix bar codes as well as machine readable fonts used in Optical Character Recognition (OCR).

Performance

HD Focal Point: 2 inches from nose
HD10 Focal Point: 3 inches from nose

HD Working Range: (typical)	6 pt OCR 20 cpi	6.6 mil QR (.017 cm)	6.6 mil Data Matrix (.017 cm)	4 mil Linear (.01 cm)
Near	2 in. (5.1 cm)	1.7 in. (4.3 cm)	1.7 in. (4.3 cm)	1.6 in. (4.6 cm)
Far	3.5 in. (8.9 cm)	2.45 in. (6.2 cm)	2.45 in. (6.2 cm)	2.7 in. (6.9 cm)

HD10 Working Range: (typical)	10 mil QR (.025 cm)	10 mil Data Matrix (.025 cm)	5 mil Linear (.013 cm)
Near	2.0 in. (5.1 cm)	2.2 in. (5.6 cm)	2.75 in. (7.0 cm)
Far	4.0 in. (10.2 cm)	3.8 in. (9.6 cm)	3.75 in. (9.5 cm)

Rotational Sensitivity: 360°

Viewing Angle: ±45°

Ambient Light: Total darkness to 100,000 lux (full sunlight)

Aiming: 660nm LEDs provide bright aiming line

Symbologies

2 Dimensional: MaxiCode, PDF417, MicroPDF417, Aztec, Aztec Mesa, Data Matrix, QR Code, Code 49, UCC Composite, Snowflake*, Vericode*, Dataglyphs*

Linear: Code 39, Code 128, Codabar, UPC, EAN, I 2 of 5, RSS, BC 412*, Code 93, Codablock
 * available to licensed users only

Postal: Postnet (US), BPO4 State, Canadian 4 State, Japanese Post, KIX (Dutch Post), Planet Code

OCR Fonts: OCR-A, OCR-B

Interfaces: RS232, Wedge, and HHLC (Code 128 Emulation)

Programmable

Options: Baud, Parity, Data Formatting, Code Options

Mechanical/Electrical**Dimensions**

Length: 4.85 in. (12.3 cm)

Height: 1.85 in. (4.7 cm)

Width: 2.50 in. (6.35 cm)

Weight w/o cord: 5.5 oz. (156 g) or less

Power Requirements: 4 to 9 volts

Current Draw: Low Power Mode - average @ 5 VDC-40mA
 Medium Power Mode - average @ 5 VDC-125mA
 High Power Mode - average @ 5 VDC-175mA

Standby Current: < 200µA @ 5V

Environmental**Temperature**

Operating: -0°C to 50°C

Storage: -40°C to +70°C

Humidity: 95% RH, non condensing at 50°C

Shock: 10 drops 5 ft. to concrete @ room temperature

ESD: Functional after 15KV discharge

Agency: FCC Class B, CE



Complies with EMC 89/336/EEC
and LVD 73/23/EEC

Worldwide Offices**Offices Serving North America**

Skaneateles Falls, NY
 Tel: +1 315 685 8945
 or, in North America: +1 800 782 4263
 sales@hhp.com
 Charlotte, NC
 Tel: +1 704 998 3998
 or, in North America: +1 800 782 4263
 sales@hhp.com

Offices Serving Europe, Middle East, and Africa

Europe
 Tel: +31 (0) 40 29 01 600
 euro_sales@hhp.com
 United Kingdom
 Tel: +44 (0) 1 925 240055
 euro_sales@hhp.com
 Ireland
 Tel: +353 (0) 502 44007
 euro_sales@hhp.com

France

Tel: +33 (0) 1 461 04111
 euro_sales@hhp.com
 Germany
 Tel: +49 (0) 7 477 151377
 euro_sales@hhp.com
 Spain
 Tel: +34 93 228 76 68
 euro_sales@hhp.com

Offices Serving Asia and the Pacific Rim

Hong Kong
 Tel: +852 2511 3050/2511 3132
 asia_sales@hhp.com
 Japan
 Tel: +813 52127392
 asia_sales@hhp.com

Offices Serving Latin America

Naples, Florida
 Tel: +1 239 263 7600
 la-sales@hhp.com
 São Paulo
 Tel: +55 11 5016 3454
 la-sales@hhp.com
 Rio De Janeiro
 Tel: +55 21 2494 7060
 la-sales@hhp.com

Web Site Address www.hhp.com

Hand Held Products, Inc. d/b/a HHP (IHHP) ©1999-2002. All rights reserved. Printed in the U.S.A.

Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.