

SCANTEAM® 3700 Series Fixed Mount CCD Bar Code Scanner



Features

Excellent Depth of Field - Longest scan range for a fixed mount CCD. Scan width increases with distance. Focused illumination for easy aiming.

Internal Decoder with Flash Memory - Decodes up to 12 symbologies. Easy and fast firmware modifications. No "chip change" required for future product enhancements. True RS-232 or PC Wedge communications.

Compact Size - Small size provides maximum flexibility and easy integration.

Rugged Design - Long life in the field.

The HHP SCANTEAM[®] 3700 fixed mount CCD bar code scanner offers flexible hardware and software for easy integration into many types of equipment. Combining the rugged durability of advanced CCD technology with HHP's world class decoding software, the ST3700 provides exceptional performance in a compact form for a variety of bar code applications.

The ST3700 Series has been designed for integration into equipment that requires bar code reading capability. The ST3700 can operate as a stand-alone sensor providing bar code information as serial data, or it can be incorporated into a PC - based system as a keyboard wedge. Applications include clinical chemistry analysis, point of sale scanning, Automated Teller Machines (ATMs), light duty conveyor scanning, and PC-based custom machinery. Whatever the application, HHP's design support, strong manufacturing skills and commitment to quality make the ST3700 an excellent choice for your next integration project.

SCANTEAM® 3700 Series Specifications

Performance

Illumination:	660nm Visible Red LEDs (light emitting diodes)	
Receive:	Standard or high resolution linear CCD (PC Wedge interface available in standard resolution only)	
Scan Width:	2.2 in. (56 mm) at contact to maximum 3.5 in. (88 mm) at 2 in. (5.1 cm) from the scanner	
Focal Distance:	Choice of 0.6 in. (1.5 cm), 1.95 in. (5.0 cm) or 3.2 in. (8.1 cm) from scanner (PC Wedge interface available in 1.95 in. focal distance only)	
Resolution:	7.5 mil (.19 mm) minimum code density typical. Higher resolution configuration available	
Minimum Reflectance Difference:	37.5% difference in bar to space reflectance	
Mechanical/Electrical		
Dimensions		
Weight:	3.8 oz. (106 g)	
Height:	1.1 in. (2.7 cm)	
Length:	2.9 in. (7.3 cm)	
Width:	3.5 in. (8.8 cm)	
Housing:	Molded polycarbonate; inserts in housing for SAE (6-32) or Metric Mounting Screws (M3.5)	
Power Requirements		
Current Draw:	250mA maximum @ 5VDC ± 10%	
Connector:	8 pin female modular	The ST3700 at a glance
Environmental		Unique CCD optics design for
Temperature		superior first-read rate
Operating:	32°F to 122°F (0°C to 50°C)	Extremely durable
Storage:	-40°F to 158°F (-40°C to 70°C)	No moving parts/No glass mirror
Humidity:	0% to 95% RH (maximum noncondensing)	Snappy - responsive, quick scanning
ESD Protection:	Functional after 15KV discharge	Integrated decoder interface
Agency Conformance:	FCC Class B	Flash memory-based firmware
Interface		
Symbologies:	UPC; EAN; Code 3 of 9; Code 128; Interleaved 2 of 5; and Codabar	
Interfaces:	True RS-232, accepts external trigger input IBM AT, XT, PS/2 PC Wedge	

CC Complies with EMC 89/336/EEC

Worldwide Offices

Offices Serving North America Skaneateles Falls, NY Tel: +1 315 685 8945 or, in North America: +1 800 782 4263 sales@hhp.com Charlotte, NC Tel: +1 704 998 3998 or, in North America: +1 800 782 4263 sales@hhp.com sales@hhp.com

Offices Serving Europe, Middle East, and Africa Europe Tel: +31 (0) 40 29 01 600 euro_sales@hhp.com United Kingdom Tel: +44 (0) 1 925 240055 euro_sales@hhp.com Ireland Tel: +353 (0) 502 44007 euro sales@hhp.com euro_sales@hhp.com

France Tel: +33 (0) 1 461 04111 euro_sales@hhp.com Germany Tel: +49 (0) 7 477 151377 euro_sales@hhp.com Spain Tel: +34 93 228 76 68 euro_sales@hhp.com euro_sales@hhp.com

Offices Serving Asia and the Pacific Rim Hong Kong Tel: +852 2511 3050/2511 3132 asia_sales@hhp.com Janan

Japan Tel: +813 52127392 asia_sales@hhp.com

Offices Serving Latin America Naples, Florida Tel: +1 239 263 7600 Ia-sales@hhp.com Ta-sales@nhp.com São Paulo Tel: +55 11 5016 3454 Ia-sales@hhp.com *Rio De Janiero* Tel: +55 21 2494 7060 Ia-sales@hhp.com

Web Site Address www.hhp.com Hand Held Products, Inc. d/b/a HHP ("HHP") [©]1999-2002. All rights reserved. Printed in the U.S.A. Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.