



TT8870 Image Kiosk™



Features

Enhance the Customer's Shopping Experience - Your customer can access a world of information with just the touch of a finger.

Enable Customer Relationship Management Administration -Market directly to your customers through advertising, coupon offerings, and loyalty program administration.

Card Reader Options - Choose a 3-track MSR or a hybrid MSR plus smart card reader.

Ease of Integration – Quickly incorporates into your existing infrastructure, saving you time and money.

Safe, Proven Technology – Fourth generation, world class imaging technology quickly scans bar codes for price checking and other applications.

Gain Valuable Sales Floor Space - Leverage the power and performance of larger kiosks while taking up far less floor space.

Increase Unattended Sales Opportunities – The 10/100 Ethernet or 802.11b channels let you send targeted advertisements in real time, increasing upsell potential.

Build a One Stop Customer Information Center – Adding a peripheral, such as a printer, allows you to expand the list of potential applications.

Future-Proof Technology - Ready for smart card implementation; Sunrise 2005 compliant.

Optional 802.11b Capability - Increases retailers' flexibility and communication capability.

HHP proudly introduces the revolutionary TT8870 Image Kiosk. The TT8870 is a fully functioning minikiosk that checks prices, interacts with the customer, and processes transactions. The TT8870 allows you to raise the customer's shopping experience to a new level. Offering the power and performance of larger, expensive kiosks, the HHP TT8870 Image Kiosk provides great value from a company you can trust.

HHP's TT8870 Image Kiosk creates a new class of interactive customer device by combining ease of use with fast data processing and low total cost of ownership. The TT8870 enhances the overall customer experience through finger touch navigation and instant on-screen feedback.

The innovative design is ergonomic, durable, and friendly to use. The TT8870 Image Kiosk can energize your marketing program awareness through scrolling advertisements and targeted sales messages.

The TT8870 Image Kiosk offers a lower cost of ownership through labor savings, increased sales, and low maintenance costs. The TT8870 joins the HHP Transaction Terminal family offering unrivaled power, versatility, value, and quality.

To learn how the TT8870 Image Kiosk can work for you, contact us at any of the locations listed on the back or visit us at www.hhp.com.

Upgrade your image.

TT8870 Image Kiosk Specifications

Display/Signature Window

Signature Window: Resistive, transparent, pressure-sensitive touch screen with replaceable screen protector system

LCD Size (Active Area): 4.45 x 3.3 in. (11.3 x 8.4 cm)

LCD Resolution: 320 x 240 dpi Touch Pad Resolution: 903 x 1238 ppi

Communications

Radio Frequency: 802.11b, optional (AC power adapter and power supply required; not included) RS-232: 4800 to 115.2 Kbps (AC power adapter and power supply required; not included)

RS-232 Pass-Through: 4800 to 115.2 KBS auxiliary Y cable (AC power adapter and power supply required; not included)

AC power adapter and power supply required; not included PC USB:

Ethernet 10/100 BaseT: Optional port; cable not available from HHP (AC power adapter and power supply required; not included)

Memory Base Flash: 4MB 16MB SRAM: 16MB 32MB

Dimensions (reference)

Width: 9.75 in. (24.8 cm) Depth: 8.6 in. (21.8 cm) Height: 3.8 in. (9.6 cm) Weight: 2.8 lb. (1.7 kg)

Power Requirements

Current Draw: 1100 mA @ 12VDC Source: 120V AC adapter

Optional Software Development Kit

Operating Systems: Microsoft® Windows® 95, Windows® 98, Windows® 2000, Windows® XP, Windows NT® 3.51 or higher

Formats Supported: BMP, CGM, DIB, EPS, MF, PCL, PCX, PLS, JPEG, and TIF.

Signature Processing

Compression: SIG - 5:1 (default), VBC - 4:1. NLC - 5:1, CMP - 10:1

Average File Size: SIG - 1600 bytes, VBC - 500 bytes, NLC - 400 bytes, CMP - 200 bytes

Security

Hardware Features: Secure key injection, tamper response, dedicated security processor

Firmware Authentication: File authentication (SHA1 and RSA at 1024 bits)

Encryption: PIN Encryption, Master/Session key, DUKPT, DES 64, and 128 bit

RF Security WEP (128 bit)

Approvals and Certifications

Agency Conformance: FCC Class A, CE (LVD), UL 1950, CSA 22.2, EMV Level 1, RSS-210.



Complies with EMC 89/336/EEC

IBM is a registered trademark of International Business Machines, Inc.

Microsoft® Windows® 95, Windows® 98, Windows® 2000, and Windows NT® are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

euro_sales@hhp.com

Spain Tel: +34 93 228 78 68

euro_sales@hhp.com

Worldwide Offices

Offices Serving North America

Skaneateles Falls, NY Tel: +1 315 685 8945 or, in North America: +1 800 582 4263 sales@hhp.com

Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263 sales@hhp.com

Offices Serving Europe Middle East, and Africa

Europe Tel: +31 (0) 40 29 01 600 euro sales@hhp.com United Kingdom
Tel: +44 (0) 1 925 240055
euro_sales@hhp.com

Italy Tel: +39 (0) 2 67 100752 euro sales@hhp.com

Offices Serving Asia and the Pacific Rim France Tel: +33 (0) 1 41 158220 Hong Kong Tel: +852 2511 3050 Germany
Tel: +49 (0) 7 477 151377
euro_sales@hhp.com

asia_sales@hhp.com Japan Tel: +813 5842 6325 asia sales@hhp.com Offices Serving Latin America Naples, Florida Tel: +1 239 263 7600

la-sales@hhp.com São Paulo Tel: +55 11 5016 3454 la-sales@hhp.com Rio De Janeiro Tel: +55 21 2494 7060 la-sales@hhp.com