

Product Profile

- Ultra compact omni-directional fixed bar code scanner
- Full 20 line scan pattern
- 20cm (8") adjustable depth of field and 20cm² (8"²) scan area
- Built-in reliability with replaceable window and 2-step sleep mode
- Universal interface system
- Low power consumption, runs from keyboard/ terminal sources
- Fast setup using EasySet® software to print and scan setup codes or download to flash
- Applications include retail POS, automated healthcare, libraries, access control, etc.



MaxiScan™ 2210 SCANNER

The MaxiScan™ 2210 is an ultra compact, cost-efficient solution for omni-directional pass through scanning. Its size and performance enables fast hands-free scanning to be integrated into any retail POS station.

The scanner measures only 7.8 x 11.5 x 6.5cm (3.1 x 4.5 x 2.6") but offers a full 20 line scan pattern, 20cm (8") depth of field and 20cm² (8"²) scan zone for easy and ergonomic scanning.

A mounting kit and Velcro pad are included for simple installation onto horizontal or vertical surfaces. The M2210's shape and size allows one of the most space saving methods of scanning—fixing the scanner to the side of the POS terminal. To further 'tune' the scanner to the POS station, the scanning depth of field can be adjusted to fit the working area and avoid accidental reads. Finally, the scanner

is supplied with a set of color profiles that can be used to customize the look of the scanner and match to other color schemes.

The M2210 has unique built-in reliability. The scanner window is replaceable in the field to avoid having to return scanners simply because of scratched windows. A two-step sleep mode provides a separate laser and motor timeout for power/life saving and instant wake-up.

A universal interface system allows the scanner to be connected to many hundreds of PC's, cash registers or other terminals simply by changing the cable and software setup.

In common with most Intermec scanners, the M2210 is supplied with EasySet® set up software for the fastest on-line or off-line configuration.

General

The MaxiScan 2210 is a high performance omni-directional bar code scanner for fixed applications

Physical Characteristics

Height: 11.5cm (4.5")
Width: 7.8cm (3.1")
Depth: 6.5cm (2.6")
Connector: 14-pin Male 2mm pitch Molex™/Berg™

Scanning Performance

Scan Pattern: 20 lines
Scan Rate: 1200 scans/s
Minimum X dimension: 0.125mm (5 mil)
Depth of field: 0 to 20 cm (8") EAN/UPC
Scan area at max depth of field: 20cm2
PCR: 25% minimum

Symbologies

UPC E,A, EAN, Code 39, Code 128, UCC EAN 128; Interleaved, Matrix, Industrial and Standard 2 of 5; Codabar, Code 93, MSI, Plessey. Others including ISBT on application

Operator Interface

Power and good read LED. Good read beeper

Design

Processor: Custom chip (ASIC inc. DSP processor) for fast signal processing and decoding. Flash memory
Light Source: visible laser diode @ 650nm, 0.45mW max output
 Laser Class 1 IEC 825 / CDRH Class IIa

Environmental Characteristics

Operating temperature: 0° to 40° C (32° to 104° F)
Storage temperature: -40° to 60° C (-40° to 140° F)
Relative humidity: 5% to 95% non-condensing
Ambient lighting: 0-100,000 lux
Drop resistance: 10 drops 1m (3.2') onto concrete. IP52 rated.

Electrical Characteristics

Power requirements: +5VDC +-5%, current consumption approx. 200mA (normally powered from host terminal)

Advanced Features

Code reconstruction, 2 step sleep mode (laser and motor) for fast wake-up and high reliability, replaceable scan window, firmware updates via flash memory, programmable data format (code identification, preambles and postambles), intercharacter and intermessage delays and many others

Interfaces

All scanner heads support (by choice of cable): Wand emulation, single or dual RS 232 C, Wyse, HP700/xx and PC AT/PS2 wedge to over 400 terminals and PCs. Extensive interface information on application

Accessories

Counter/wall mount bracket (standard), velcro pad (standard), interface cables, color profiles (standard), spare window (one spare included as standard), external power supplies (option)

Configuration

Setup options include EasySet® PC software, by direct connection & bar code printing (custom setup utility), or by conventional bar code setup manual

Regulatory Approvals

All models: Compliant with all European Directives: CE (EN50081-1/ EN50082-1/ EN60950/ CE174-2). TÜV-Rheinland Safety certified.
USA: FCC Part 15 Certified: Class B digital device. UL listed.
Canada: ICES-003, NMB003: Class B digital apparatus. cUL listed.
Australia and New Zealand: AS/NZS 3548 C tick marked
 Other approvals pending.
 DHHS Standard 21CFR 1040.10 and 1040.11 Class IIa Laser Product
 IEC 825-1, EN60825-1, Class 1 Laser Product

LASER LABEL:

IEC825-1 (1993) – EN60825-1 (1997)
 Class 1 Laser Product
 Appareil Laser de Classe 1 - Laser Produkt der Klasse 1
 US: Complies with US DHHS Standard 21 CFR Part 1040 as a: Class IIa Laser Product.

Avoid long term viewing of direct laser radiation.
 Éviter toute exposition prolongée de la vue au rayonnement laser direct.
 Augen vor direktem Laserlicht schützen.

North America

Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

Systems & Solutions
 550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies
 9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Canada
 7065 Tranmere Drive
 Mississauga, Ontario
 L5S 1M2 Canada
 tel: 905.673.9333
 fax: 905.673.3974

Europe/ Middle East & Africa

Headquarters
 Sovereign House
 Vastern Road
 Reading RG1 8BT
 United Kingdom
 tel: 44.118.987.9400
 fax: 44.118.987.9401

Asia Asia Regional Office
 26-16 International Plaza
 10 Anson Road
 Singapore 079903
 tel: 65.6324.8391
 fax: 65.6324.8393

Intermec International, Inc.
 14 Floor, IBM-Pacific Century Place
 2A Workers Stadium
 Chaoyang District, Beijing 100027
 P.R. China
 tel: 86.010.6539.1012
 fax: 86.010.6539.1025

Australia

Level 7, 200 Pacific Highway
 Crows Nest, NSW 2065
 Australia
 tel: 61.2.9492.4400
 fax: 61.2.9954.6300

South America & Mexico Intermec South America Ltda.

Rua Arandu 1544-15 andar
 Edificio Itavera
 Brooklin Novo 04562-031
 Sao Paulo, SP
 Brazil
 tel: 55.11.5501.2070

Intermec Technologies de Mexico
 Tamulipas 141, Primero Piso
 06140 Mexico, D.F.
 tel: 525.55.211.1919
 fax: 525.55.211.8121

Worldwide

Fax Document Retrieval Service
 800.755.5505
 (North America Only)
 tel: 650.556.8447

Internet
 www.intermec.com

Sales
 800.347.2636
 (toll free in N.A.)
 tel: 425.348.2726

Service and Support
 800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Copyright © 2003 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.
 611030-01B 09/03

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.