



Intermec

Product Profile

- Small, lightweight design
- Newest IEEE 802.11 wireless standards
- Industry standard development and connectivity tools
- Upgradeable wireless and batch versions provide investment protection
- Long lasting Lithium Ion battery for full shift operation
- Survives 4-foot drops to concrete



2 4 1 0 H A N D H E L D C O M P U T E R

With its compact, lightweight packaging, the 241X Series handheld computers are designed for retail and light industrial environments. Weighing under 14 oz., the 241X Series provides easy operation over extended periods.

The 241X Series handheld computers share applications with other members of 2400 family. You can run the same application on a stationary shop floor terminal, a 241X Series handheld computer, and a vehicle mount unit.

With its industry-standard internal PC card slot, the 241X Series can adapt with your system as your data collection needs change. You can start with the 2410—a hardwired (batch) system—and upgrade to the 2415—an 802.11b 11Mbps standard wireless system—simply by sending it to an Intermec service center for an RF

upgrade. The 2415 can also be upgraded with the latest technology so you can easily change radios to handle higher speeds and increased coverage as advances in standards such as 802.11 RF technology occur.

You can also count on the 241X Series to put in a full day's work without recharging. Its state-of-the-art Lithium Ion battery is easy to recharge and can run 8 to 10 hours on a single charge. That makes the 241X ideal for time-intensive applications, such as in-store audits and re-stocking inventory. And its high-contrast, scratch resistant display makes for easy reading in many environments. Best of all, 241X Series handheld computers integrate seamlessly into your system, whether it is terminal emulation, client/server or simple serial connection through a communications dock.

A large, stylized outline of the Intermec logo at the bottom of the page.

Physical Characteristics**Length:** 19.3 cm (7.6")**Width:** 8.4 cm (3.3") at scanner; 5 cm (2") at grip**Height:** 5.6 cm (2.2") at scanner; 3 cm (1.2") at grip**Weight (with standard battery):****Model 2410 (Batch):** 374g (13.2 oz.)**Model 2415 (RF):** 422g (14.9 oz.)

Add 43g (1.5 oz.) for high capacity battery

Environment**Operating temperature:** -20° to 50°C

(-4° to 122°F)

Storage temperature: -20° to 60°C

(-4° to 140°F)

Humidity: Non-condensing (0 to 95% RH)**Shock and Vibration Protection:**


Warranted for 4-foot drop to concrete

Power**Operating:** Lithium Ion battery pack, standard and high capacity**Memory****RAM:** 1 MB, battery backed**Non-volatile Memory:** 2MB Standard, 4MB optional**Additional Storage:** 2 or 4MB SRAM (batch only)**Interfaces**

- Built-in serial connector, 9-pin adapter optional
- RS232-C up to 38.4 Kbps
- XMODEM, YMODEM for data transfer
- Supports configurable Serial Protocol and XON/OFF

Display

- CGA compatible backlit LCD displaying 16 lines of 20 characters per line (160 x 128 dot matrix) plus LED status indicators
- Full 25 x 80 virtual screen with viewporting

**North America**

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies

9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

Canada

7065 Tranmere Drive
Mississauga, Ontario
L5S 1M2 Canada
tel: 905.673.9333
fax: 905.673.3974

Europe/**Middle East & Africa**

Headquarters
Sovereign House
Vastern Road
Reading RG1 8BT
United Kingdom
tel: 44.118.987.9400
fax: 44.118.987.9401

Asia

Asia Regional Office
26-16 International Plaza
10 Anson Road
Singapore 079903
tel: 65.6324.8391
fax: 65.6324.8393

Intermec International Inc

14 Floor, IBM-Pacific Century Place
2A Workers Stadium
Chaoyang District, Beijing 100027
P.R. China
Tel: +86 (010).6539 1012
Fax: +86 (010).6539 1025

Keyboard

- Elastomeric 55-key with full alphanumeric set or 37-key with larger numeric.
- Options for U.S., Multilingual European, IBM 3270/5250, and VT/ANSI

Software**Programmable:** Microsoft® C**Terminal Emulation:** 3270 and 5250 SNA

and TELNET; ANSI/VT 100, 220, 320 TELNET;

Screen mapping

Web-based: dc Browser™ for HTML applications**Connectivity**

- DHCP Client
- Direct TCP/IP Support
- Sockets interface or terminal emulation
- Ethernet or Token Ring

Bar Code Symbologies

Code 39, 2 of 5, Interleaved 2 of 5, Codabar, UPC/EAN Code 128, Code11, Code 93, Plessey, MSL, PDF 417

Bar Code Scanning Options

Integrated visible laser diode scanner

USA/Canada Class II. International Class 2

Depth of Field-Standard Range***(670nm) (measured for Code 39)**

| | | |
|-------------------------|--------------|-------------|
| 5 mil | 9.4-15.7 cm | (3.7"-6.2") |
| 10 mil | 7.4-30.5 cm | (2.9"-12") |
| 20 mil | 10.2-63.5 cm | (4"-25") |
| 30.0 mil | 10.2-86.4 cm | (4"-34") |
| 40.0 mil | 12.7-99 cm | (5"-39") |
| 55.0 mil | 19.1-126 cm | (7.5"-49") |
| 55 mil retroreflective | 105-151 cm | (41"-59") |
| 100 mil retroreflective | 113-227 cm | (44"-89") |

Depth of Field-Long Range* (650nm)

| | | |
|-------------------------|----------------|----------------|
| 10 mil | 29.4-49.8 cm | (11.6-19.6") |
| 20 mil | 21.8-98 cm | (8.6 - 38.6") |
| 30 mil | 24.4-192 cm | (9.6 - 75.6") |
| 40 mil | 24.4-204.7 cm | (9.6-80.6") |
| 70 mil retroreflective | 192-410.5 cm | (75.6-162") |
| 100 mil retroreflective | 212.3-532.4 cm | (83.6"-209.6") |

*Measured for Code 39

Built-in 16 pin I/O connector for attaching Intermec decoded and undecoded scanners and wands. Adapter available.

Integrated RF Module: (2415)**Frequency:** 2.4 GHz frequency band, actual frequencies in use vary by country**WLI forum OpenAir:****Type:** Frequency Hopping Spread Spectrum**Data Rate:** 1.6 Mbps, .8 Mbps fallback**Range*:** From 1500+ ft. (450+ m) to 500 ft

(150 m) depending on environment

IEEE 802.11b Wi-Fi Certified:**Type:** Direct Sequence Spread Spectrum**Data Rates:** 11/5.5/2/1 Mbps with Auto fallback for increased range**Range* at 1 Mbps:** 1750 ft (533 m) to 165 ft

(50 m) depending on environment

Range* at 11 Mbps: 525 ft (160 m) to 80 ft

(24 m) depending on environment

Security: Wired Equivalent Privacy (WEP) -

64 or 128 bit encryption

*Unlimited with roaming

Host Support via DCS300 Server**Host Environment:** IBM AS 400, Digital HP,

UNIX, Windows NT

Connectivity: Ethernet, Token Ring,

100BASET, Twinax, Coax, SDLC

Communications: TCP/IP, SNA**Accessories**

Battery charger, battery pack available in standard and high capacity, pistol grip handle, holster, belt loop, hand strap, serial communications dock, User manual, Programmer's Software Kit (PSK).

Regulatory Approvals

UL Listed, UL 1950 and C22.2 No. 950, TÜV GS Licensed, EN 60950 and EN 60825-1, FCC Part 15, Canada, RSS210 and ICES-003, Class B, EN 55022/CISPR 22, Class B, ETS 300 328, ETS 300 826, Compliant with all European directives, CE marked.

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

Worldwide

Fax Document Retrieval Service
800.755.5505
(North America Only)
tel: 650.556.8447

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2004 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611030-01C 03/04

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

Intermec
e x p e c t MORE™