

Intermec

Product Profile

- Open systems
- Small, lightweight and economical
- Touch screen, keypad or scanner for flexible data input
- Complete line of peripherals and accessories
- Low lifetime cost of ownership



600 SERIES PEN COMPUTER

Palm-Sized Functionality

Intermec® 600 Series combines the advantages of consumer personal digital assistants (PDAs) and high performance industrial pen computers. It's small and lightweight while offering rugged design, integrated keypad, barcode scanning and enhanced connectivity.

Multiple Vertical Applications

The touch screen, graphical user interface and signature capture capability make the 600 Series ideal for those who require forms based data collection in a convenient compact package. From order taking in retail and point-of-care in healthcare to quality control and incoming inspection in manufacturing and warehousing, the Intermec 600 Series empowers frontline workers on the go to achieve greater productivity.

Based on the Windows® CE operating system, applications can be developed quickly and easily using the latest development tools and network connectivity such as Visual C++, Visual Basic,

HTML and TCP/IP. Whether operating the computer indoors or out, the large backlit touch display allows the use of symbols and icons to make it easy for workers to learn and navigate application.

Flexible Input Methods

The tactile 16-hard surface key keypad and optional integrated scanner provide efficient input of numeric and bar code data. Scanner trigger and up/down cursor buttons are positioned on the side for true one-handed operation.

Complete System

Part of a complete computing solution, the 600 Series supports vehicle or fixed docking, scanning and printing. Intermec 600's modularity and open systems architecture ensure years of operation and a smooth migration to new technologies.

Intermec

Physical Characteristics**Length:** 15.5cm (6.1")**Width:** 9.1cm (3.6")**Depth:** 3.0cm (1.2")**Weight:** 312g with battery (11oz.)**Environment****Operating Temperature:** -20° to +60°C

(-4° to +140°F)

Storage Temperature: -30° to +70°C

(-22° to +158°F)

Relative Humidity: 5% to 95 %

(non-condensing)

Drop Spec: Withstands 1.2m (4') drop to a hard surface**Operating Altitude:** -100 to 5000m (-328' to 16,404')**Operating System****601:** MS-DOS® 6.22**602:** Windows® CE 2.12, MS-DOS 6.22 or Windows® 95**Microprocessor****601:** AMD SC 400 486@33MHz**602:** AMD SC 400 486@66MHz**Memory****601:** 8MB RAM, 8MB Internal Compact Flash**602:** 16MB RAM, 16MB Internal Compact Flash, External Compact Flash slot**Display**

- 240 (width) x 320 (length) pixels 9.5cm (3.75") diagonal
- Monochrome LCD
- Electroluminescent (EL) backlight

DigitizerHigh resolution touch screen
(Passive stylus or finger tip)**Battery Power**

- Internal 1550 mAh Lithium-Ion rechargeable battery pack
- 4 hour charge

Keypad

- 16 hard surface keys
- Side buttons for cursor up/down and enter/action
- Scanner trigger button

Input Device

Touch screen, keypad, optional integrated scanner

Scanner**602:** Optional integrated standard range VLD scanner**Docking Solutions**

- Desk/Vehicle dock provides charging, Ethernet 10-BaseT LAN connectivity and serial RS-232 connectivity
- Depot dock holds 4 computers and provides charging along with optional LAN connectivity with both 10-BaseT Ethernet and RS-485 Multi-drop

Accessories

AC adapter

Auto adapter

Holster

Cables: Serial, data sync and DEX/UCS

Impact receipt printer

Thermal receipt printer

Impact page printer

Display protector kit

Regulatory Approvals

FCC Class B, UL Listing, CE Mark, CB Report

Note

Some approvals and features may vary by country and may change without notice. Please check with your local Intermec sales office for further information.

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies

9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

**Europe/
Middle East & Africa**

Headquarters
Sovereign House
Vastern Road
Reading, Berkshire RG1 8BT
United Kingdom
tel: +44.118.987.9400
fax: +44.118.987.9401

Gothenburg

Idrottsvägen 10
P.O. Box 123
SE-431 22 Mölndal
Sweden
tel: +46.31.869500
fax: +46.31.869595

**Asia Pacific/
Latin America**

Hong Kong
26-12 Shell Tower
Times Square
1 Matheson Street
Causeway Bay
Hong Kong
tel: 852.2574.9777
fax: 852.2574.9725

Singapore

25-16 International Plaza
10 Anson Road, 079903
tel: 65.324.8391
fax: 65.324.8393

Australia

Level 7, 200 Pacific Highway
Crows Nest NSW 2065
Australia
tel: 61.2.9901.2065
fax: 61.2.9954.6300

South America and Mexico

2572 White Road
Irvine, California 92614
tel: 949.975.1905
fax: 949.975.1913

Worldwide**Fax Document Retrieval Service**

800.755.5505
(North America Only)
tel: 650.556.8447

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
425.356.1799

Copyright © 2001 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608876-01B 05/01

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.