

PRINTERS

Intermec® 6804T/DM

Features:

- Rugged design built for field environment
- Lightweight, belt-clip configuration provides medium portability for the user
- Rechargeable battery provides ample power for all-day printing
- Wireless I/R interface to mobile computer and belt-clip design allows for hands-free mobility



Small, Light and Durable

The Intermec® 6804T (thermal) and Intermec® 6804DM (dot matrix) printers are small, light durable units that can be taken anywhere your busy field representatives need them. They quickly print both standard and bar coded receipts to exact specifications.

Belt-Clip Design for Easy Use

The Intermec 6804T/DM wireless interface and belt-clip design allow the driver/salesperson to easily carry both the mobile computer with printer and product into the customer location in one trip.

Reliable Quality

The reliable printer mechanism of the Intermec 6804T and Intermec 6804DM enables use in the challenging delivery environment. This durability does not come at the expense of print quality, as the printer offers exceptional print clarity and the versatility of graphics capability for logos and even bar codes.

Long-Lasting Power Supply

The automatic power saving sleep mode and vehicle charger option creates the perfect system for a long day in the field.

Paper Changes are Made with Ease

The functional design of the printer cover on the Intermec 6804T/DM printer makes paper loading extremely simple. Roll type paper fits effortlessly into place.

All of these features combine to make the Intermec 6804T/DM printer the logical choice for those users who need maximum portability, minimum size and the ability to withstand the challenging environmental conditions which exist in distribution applications.



Intermec® 6804T/DM



Physical Characteristics

Length: 18.1cm (7.1")
Width: 11.7cm (4.6")
Depth: 4.6cm (1.8")
Weight: 590g (20.8oz)

Environment

Operating Temperature:
 6804T: 5° to 122° F (-15° to 50°C)
 6804DM: 32° to 122° F (0° to 50°C)
Drop Spec: Withstands multiple 152cm (5') drops to concrete

Power Source

Internal battery, NiMH 1.8 amp/hr
 User replaceable

Battery Recharging

Nine hours to full charge using a vehicle cigarette lighter power adapter or standard AC power adapter

Printer Mechanism

Characteristics:
 6804T: Direct thermal line printer
 203 dots per inch (dpi)
 6804DM: Impact dot matrix printer
 240 dots per line (dpl)
Print Speed: 3.8cm (1.5") per second

Fonts

Three resident fonts
 Up to four additional fonts may be downloaded

Print Capabilities

6804T: Characters, graphics and bar codes
 6804DM: Characters

Print Medium

6804T: Thermal paper, one ply
 6804DM: Normal paper, one- or two-ply
Paper Width: 5.7cm (2.25")

Print Duration Per Charge

6804T: Over 9144cm (3,600")
 6804DM: Over 3048cm (1,200")

Interface

IrDA®
 RS-232C serial

Chargers

AC wall charger
 12V vehicle charger

Agency Approvals

FCC Part 15J, Class B

Note

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

North America • Intermec Technologies Corporation • Systems & Solutions • 550 2nd Street S.E. • Cedar Rapids, Iowa 52401 • 1 (800) 452-2757 tel • 1 (319) 369-3453 fax • Accessories: 1 (800) 255-6292 tel • 1 (319) 369-3625 fax • Label Products: 1 (800) 227-9947 tel • 1 (513) 874-8487 fax • Amtech Systems Division • 19111 Dallas Parkway, Suite 300 • Dallas, TX 75287-3106 • (800) 923-4824 tel • (972) 733-6699 fax

Europe/Middle East/Africa • Sovereign House • Vastern Road • Reading RG1 8BT Berkshire • United Kingdom • +44 118 987 9400 tel • +44 118 987 9401 fax • Label Products: +31 24 3723 100 tel • +31 24 3780 070 fax

Asia Pacific/Latin America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax • Label Products: 1 (800) 227-9947 tel • 1 (513) 874-8487 fax

World-Wide Fax Document Retrieval Service • 1 (650) 556-8447 tel • 1 (800) 755-5505 (North America Only)

Internet • www.intermec.com **E-mail** • info@intermec.com

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice. Copyright © 2000 Intermec Technologies Corporation. All rights reserved. Intermec® is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in U.S.A. #960-701-031 (01/00)