

Product Profile



- Lightweight, ergonomic design allows for single-handed operation
- Choices of integrated bar code scanner or imager
- Large 160 x 160 display for flexibility in application design
- Customize with a flexible rapid development tool
- Linux® based operating system
- Powerful 67 MHz processor to support large look-up tables or data storage
- Choice of data communication docks

CK1 HANDHELD COMPUTER

Companies of all sizes can now realize the benefits of automatic data collection with the CK1, a powerful and flexible batch data collection terminal for retail, light industrial, and medical/pharmaceutical applications requiring small-sized ergonomics at an economical price. With choices of simplified programming tools or pre-loaded applications, linear imager or bar code scanner, along with large memory and a crisp display, Intermec's CK1 can benefit the bottom line through increased employee productivity and inventory accuracy.

The CK1 offers features and functionality found in terminals much larger and more costly. With an ergonomic keyboard and a pocket-sized form factor, the CK1 allows for easy single-handed operation when it is demanded. An optional removable pistol grip handle is available for scan intensive applications.

The CK1 has a choice of bar code input options: an integrated laser scanner, or a highly responsive linear imager, offering safe user interaction and aggressive decoding performance. The large, scratch-resistant 160 x 160 pixel display with backlight provides user-friendly navigation in all lighting conditions, as

well as flexibility in application design. Continuing the Intermec legacy of rugged construction, the CK1 withstands multiple 1.2-meter (4-ft) drops to a hard surface.

Users will appreciate the simplicity of pre-written batch applications, powerful rapid application development tools or extensive SDK for flexible application choices offered by the CK1. It combines a Linux® based operating system and Linux® programming tools to provide a powerful and flexible open source platform for rich end-user applications with multi-tasking capabilities. Use CK1 right out of the box with pre-written programs for various applications, or for powerful and rapid application development, a Windows® based rapid development tool can be purchased that requires no programming experience.

Intermec's CK1 has a powerful ARM 7, 67 MHz processor with 16MB DRAM and 9MB Flash to support large look-up tables or data storage. A replaceable Lithium-Ion battery supports extended rigorous use and a fast 3-hour recharge.

Numerous docking options are available including a single-slot RS-232 or modem dock and a multi-slot USB charging dock.

Physical Description

The ergonomic, pocket-sized CK1 is a fully functional Linux based computer for efficient, automated batch data collection. With large display, and choice of integrated bar code scanner or linear imager, the CK1 is ideal for parcel pickup and delivery, light industrial, and retail inventory management.

Physical Characteristics

Length: 190 mm (7.5")

Height: 35 mm (1.35")

Width: 73 mm (2.88")

Depth: N/A

Weight: 218 g (7.68 oz.) including battery

Power

Supply: 900 mAh (3.6V) rechargeable

Lithium Ion (Li-Ion) battery pack

Battery Life: Extended shift (12 hour)

Power Management: Auto-suspend

AC Adapter/Recharging: 3-4 hour recharge time

Environment

Operating Temperature: -10° to 60° C

(14° to 140° F)

Storage Temperature: -20° to 70° C

(-4° to 158° F)

Recharging Temperature: 0° to 50° C

(32° to 122° F)

Humidity: 0 to 95% relative humidity (non-condensing)

Rain and Dust Resistance: Designed to IP42

Drop Survival: Designed for multiple 1.2m (4-ft) drops to concrete

Hardware

Memory: 16MB DRAM

Non-volatile Flash Memory: 9MB

Microprocessor: 67 MHz ARM 7 Processor

Operating System: Embedded Linux

Operating System, EsFia uCLinux

Version 2.4

Display: Monochrome, anti-glare LCD display capable of configurable graphics and supporting up to 16 lines by 20 characters (160 x 160 pixels) with auto-off EL backlighting and scratch resistance surface.

Keyboard: 29 hard top keys including single Enter/Scan button, Numeric keys, with shift alpha, 4 navigation keys and 4 function keys

Beeper: User programmable volume, pitch and duration

LED: Tri-state software programmable LED to indicate good/bad read/communication

Software

Development Environments:

Microsoft® C application development under Windows 2000, XP

Software Development Kit (SDK)

MCL Rapid Development Tool Kit for application program development

International Support

English / Western European languages

Japanese, Traditional Chinese (Big 5),

Chinese Simplified, Thai (future)

Connectivity

TCP/IP over PPP using the following transports: RS232 direct single dock, USB multi dock, RS232 modem or *Bluetooth™.

TCP/IP over PPP GPRS using either a Bluetooth or tethered GPRS mobile phone.

Z-Modem communication protocols using either RS232 direct single dock, USB multi dock, RS232 modem or Bluetooth.

Security

Administrative password protection optional

Bar Code Symbolologies

Code 39 Standard and Full ASCII, Codabar, UPC/EAN, UCC/EAN128, Interleaved 2 of 5, Code 32, Standard 2 of 5, Code 93, Code 128, MSI, Plessey, China Postal Code, RSS14

Characters/Fonts

Font 1: Courier 6x8, 20 lines, 26 columns

Font 2: Courier 8x16, 10 lines, 20 columns

Bar Code Scanning Module Options

Integrated Linear Imager

Integrated Standard Range Visible Laser (650nm)

Scanning Performance

Scan rate: Linear Imager – 270 scans/second

Scan rate: Visible Laser – 39 scans/second

Wireless PAN

Optional integrated Bluetooth™ compatible module (Serial Port Profile)

Accessories

Communication/Charge Dock: Single RS-232, V90 Modem

Multi-Dock: Four Cavities (Daisy Chain) USB Wrist Strap (Standard)

Scan Handle

Single Battery Charger

Cell Phone data cable

Printer cable

Regulatory Approvals

Electrical: CE Compliance

Emissions: FCC Part 15 – Class A

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

*Bluetooth is a trademark owned by Bluetooth SIG, Inc., USA.

Intermec[®]
e x p e c t MORE™

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies

9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

Canada

7065 Tranmere Drive
Mississauga, Ontario
L5S 1M2 Canada
tel: 905.673.9333
fax: 905.673.3974

Europe/**Middle East & Africa**

Headquarters
Sovereign House
Vastern Road
Reading RG1 8BT
United Kingdom
tel: 44.118.987.9400
fax: 44.118.987.9401

Asia

Asia Regional Office
26-16 International Plaza
10 Anson Road
Singapore 079903
tel: 65.6324.8391
fax: 65.6324.8393

Intermec International Inc
14 Floor, IBM-Pacific Century Plaza
2A Workers Stadium
Chaoyang District, Beijing 100027
P.R. China
Tel: +86 (010).6539 1012
Fax: +86 (010).6539 1025

Australia

Level 7, 200 Pacific Highway
Crows Nest, NSW 2065
Australia
tel: 61.2.9492.4400
fax: 61.2.9954.6300

South America & Mexico

Intermec South America Ltda.
Rua Arandu 1544-15 andar
Edifício Itavera
Brooklin Novo 04562-031
Sao Paulo, SP
Brazil
tel: 55.11.5501.2070

Intermec Technologies de Mexico

Av Tamaulipas #141, Primer Piso
Col. Hipodromo Condesa
Mexico, DF, 06140 Mexico
tel: 525.55.211.1919
fax: 525.55.211.8121

Worldwide

Fax Document Retrieval Service
800.755.5505
(North America Only)
tel: 650.556.8447

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2003 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611405-01A 11/03

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.