

- Superior throughput eliminates wait time at the printer
- Compact size for demanding applications where space is limited
- Supports stand-alone printer applications
- Easily adapts to changing host environments and applications
- Can emulate and replace competitive and older Intermec printers
- CompactFlash memory for quick and easy firmware, font, and memory upgrades
- Utilizes up to five interface ports simultaneously, including internal EasyLAN™ Ethernet or EasyLAN Wireless
- Magnetic QuickMount™ printhead for easy printhead installation
- User selectable printer language

The EasyCoder PF4i is designed to excel where space is limited. Utilizing the latest technology, it features a strong and proven mechanical platform, and powerful newly developed electronics.

The EasyCoder PF4i can act as a "smart client" executing user-defined programs. This means that your printer can eliminate the PC, operate additional hardware (e.g. scanners, other printers, conveyors), access information from the network, and has the ability to change with the application for additional functionality when needed. When using the EasyLAN Wireless option, any attached peripheral devices also become part of the wireless infrastructure.

Printer command languages do not restrict the EasyCoder PF4i. The PF series printers can emulate and replace competitive and older Intermec printers without requiring any changes to the host programming or label formats.

The EasyCoder PF series features optional integrated wired or wireless EasyLAN networking. The wireless interface uses an integrated standard 802.11b/g radio providing 128-bit WEP encryption of the information relayed through the network.

The magnetic QuickMount printhead eliminates hassles and downtime. The printhead is replaced quickly and easily with the magnet and u-brackets ensuring proper alignment. The double-clutching ribbon mechanism means that you are not restricted to ribbon types based on how they are wound. The handy, inexpensive and PC-compatible CompactFlash™ memory technology provides quick and easy memory expansion for extra storage of formats, graphics, fonts, and provides an easy way to update printer firmware.

The EasyCoder PF4i bar code printer is exceptionally fast in throughput and printing, reliable, and delivers very high print quality.



Application

Direct Thermal and Thermal Transfer label, ticket and tag printer.

Physical Characteristics

LxHxW: 405 x 178 x 244 mm (15.9 x 7.0 x 9.6 in) Weight: 8 kg (17.7 lbs.)

Print Specifications

Max. Width: 104 mm (4.09 in) at 203 dpi; 105.7 mm (4.16 in) at 300 dpi.

Max. Length w/ std memory: 2520 mm (99.2 in) at 203 dpi; 1092 mm (43.0 in) at 300 dpi.

Max length w/ 16MB SDRAM: 4095 mm (161.2 in) at 203 dpi; 2730 mm (107.5 in) at 300 dpi.

Up to 76 labels per minute. 101x152mm (4x6 in) GM1724 label. To learn more, please visit www.intermec. com/printspeed.

Print Direction

Prints smooth text, any size bar codes and graphics in all four orthogonal directions.

Print Resolution

8 dots/mm (203 dpi), 11.8 dots/mm (300 dpi)*

Label/Ticket/Tag

Max. Width:114.3 mm (4.5 in) Min. Width: 25.4 mm (1 in) Thickness: 2.5 to 8.7 mil

Style: Roll-fed, die-cut, continuous or fanfold labels,

tags or tickets

Label Roll max diameter: 150 mm (6.0 in) Label Roll Core: 38-76 mm (1.5-3 in) Media Type: Thermally sensitive media

Ribbon Roll

Ribbon roll max diameter: 65 mm (2.56 in) or approx. 300 m (980 ft) of ribbon

Ribbon Roll Core: 25 mm (1 in) Ribbon Type: Wax, wax/resin, resin

Interfaces

Standard:

- RS-232, up to 115.2 kB/s
- Wand interface for EasySet™ System

Optional:

- EasyLAN Wireless internal Ethernet
- EasyLAN 10/100BaseT internal Ethernet

Optional interface card adapters:

- Parallel IEEE 1284
- Industrial Interface (8 digital in/out, 4 analog relays, 1RS232/422/485 port)

North America

Corporate Headquarters

600136th Avenue West Everett, Washington 98203 Phone: (425) 348-2600 Fax: (425) 355-9551

South America & Mexico **Headquarters Office**

Newport Beach, California Phone: (949) 955-0785 Fax: (949) 756-8782

Europe/Middle East & Africa Headquarters Office

Reading, United Kingdom Phone: +44 118 923 0800 Fax: +44 118 923 0801

Asia Pacific

Headquarters Office Singapore Phone: +65 6303 2100 Fax: +65 6303 2199

www.intermec.com Worldwide Locations: www.intermec.com/locations Dual Serial ports RS-232, RS-422, RS-485 and 20mA Current Loop

Network Interface Options:

EasyLAN integrated Ethernet: RJ-45 connector for 10BaseT or 100baseTX

EasyLAN Wireless:

- Fully integrated IEEE 802.11b/g
- WEP 128 bit
- Multiple industrial antenna options for maximized coverage

Supported Protocols

TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMP, SMTP. SNMP-MIB II supported (over UDP/IP), private enterprise MIB included

Software

Available printer command languages:

- IPL
- Fingerprint/Direct Protocol

Applications/Drivers (comes on Printer Companion CD) including:

- InterDriver™ Windows printer driver
- Intermec LabelShop® START label design and print package
- Intermec Printer Network Manager for administration of networked printers
- PrintSet for printer configuration

Optional software for application development:

- Fingerprint ApplicationBuilder™
- Intermec Printer Application Server™
- ERPLabel™ for SAP™ R/3®.

Bar Code Symbologies

Fingerprint/DP 1-dimensional: Codabar, Code 11, Code 39, Code 39 full ASCII, Code 39 w. checksum, Code 93, Code 128, Code 128 Subset A-C, DUN-14/16, EAN-8, EAN-13, EAN-128, EAN-128 Subset A-C, Five-Character Supplemental Code, Industrial 2 of 5, Industrial 2 of 5 w. checksum, Interleaved 2 of 5, Intereaved 2 of 5 w. checksum, Interleaved 2 of 5 A, Matrix 2 of 5, Postnet, Straight 2 of 5, Two- Character Supplemental Code, UCC-128 Serial Shipping Container Code, UPC-5 digits Add- On Code, UPC-A, UPC-D1 to D5, UPC-E, UPC Shipping Container Code

Fingerprint/DP 2-dimensional: Code 16K, Code 49, Data Matrix, MaxiCode, MSI(modified Plessey), PDF 417, Plessey, QR Code, MicroPDF417

IPL 1-dimensional: Codabar, Code 11, Code 39, Code 93, Interleaved 2 of 5, Code 2 of 5, Code 128, UCC-128 Serial Shipping Container Code, UPC/EAN Codes(EAN 8, EAN 13, UPC Version A, UPC Version E), HIBC Code 39, Postnet, HIBC Code 128

IPL 2-dimensional: Code 16K, Code 49, PDF417, Maxicode, JIS-ITF, Data Matrix, QR Code, MicroPDF417

Sales

Toll Free NA: (800) 934-3163 Toll in NA: (425) 348-2726 Freenhone ROW: 00 800 4488 8844 Toll ROW: +44 134 435 0296

OFM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505 Toll in NA: (425) 356-1799

Standards Supported

UPC/EAN Shipping Container; UCC/EAN 128 Serial Shipping Container; MH10.8 Shipping Label; AIAG (shipping parts label); LOGMARS; POSTNET; HIBCC; ISBT 128; GM1724; UPS shipping label; Global Transport label

Character Sets

Fingerprint/DP: 15 TrueDoc™ (scalable) fonts including 12 UNICODE (1 WGL4), 1 symbol, 1 OCR-A, 1 OCR-B. Font cache for maximum performance. ATF font support. Non-Latin fonts are available as options. IPL: 13 TrueDoc (scalable) fonts + 20 bitmap fonts.

Graphics

Supports PCX file format.

Memory

Standard: 4MB Flash memory 8MB SDRAM 1 Compact Flash slot

Optional: Flash memory: Up to 16MB totally.

(8+8MB)

1GB CompactFlash memory

SDRAM: Up to 16MB totally

Protocol

Fingerprint/Direct Protocol: XON/XOFF, ENQ/ACK, DTR, RTS/CTS

IPL: XON/XOFF, Intermec Std. Protocol

Back-lit LCD for 2x16 characters and 3 LED indicator

Keypad Control Panel

- Full keypad control panel (Fingerprint/DP)
- Simplified keypad control panel (IPL)

Power Supply

115/230VAC auto-switch w/PFC Voltage Range: 100-240 VAC ±10%. Frequency Range: 45-65 Hz

Operating Environment

Temperature: +5° to +40°C (+40° to +104°F) Humidity: 20-80% RH non-condensing Noise: 50 dB (printing), no noise standby

Regulatory Approvals

CE (EN55022 Class A), FCC Class A, UL, CSA, C-Tick

Integral Self-Strip Unit with Liner Takeup, Label Taken Sensor (LTS), CompactFlash (CF) Memory, Flash and SDRAM SIMM, Various International Double Byte Fonts*, EasySet Bar Code Wand*, External RS-232C Alphanumeric Keyboard*, Parallel Interface Board, Additional Serial Interface Board*, Industrial Interface Board*, Real Time Clock, Media Supply Hub, Cutter

*Not applicable when using IPL firmware

Copyright © 2007 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611556-01C 06/07

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.





Phone: 1-800-351-9962 Fax: 1-312-212-1800

About BarcodesInc

Who We Are

BarcodesInc is North America's leading provider of •] ^& \hat{a} \hat{a}

We Owe Our Success To You

Why Choose BarcodesInc?

Dedicated Account A UbU[Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

Highly-Trained Technical Support

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same & È

Premier Access to Top Manufacturers

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

Responsive Customer Service

Every phone call and email is responded to promptly, completely and accurately by our customer service & æ È

Easy Returns

Damaged, defective or incorrectly ordered goods may be returned without hassle.

BRANDS





Intermec

Honeywell

ODATALOGIC.











unitech





Microsoft*



symbol*

AND MORE