



Intermec

Product Profile



- Rugged housing built for the field environment
- Weather resistant and highly functional
- Workboard style has holder for the 700 Series Mobile Computer
- 4" (10.2 cm) paper width capability
- 40-column format, with optional compressed 80-column capability
- Magstripe card reader option

P W 4 0 F O U R (4) I N C H W O R K B O A R D P R I N T E R

The Intermec PW40 thermal workboard printer is the newest addition to the Intermec line of workboard printers, designed specifically to hold the new Intermec 700 Series Mobile Computer. With a design that is both durable and weather resistant, the PW40 can take the punishment of daily work environments and is easily incorporated into the field. In addition, its functional design makes paper loading simple because roll-type paper fits easily into place.

The rugged one-piece solution allows the user the convenience of a joined device, with a hand strap. Additionally, the user can charge both the printer and mobile computer with one charge source.

The reliable four inch thermal printer mechanism on the PW40 offers exceptional print clarity with the versatility of printing text, graphics

and logos. It can quickly print standard 40-column receipts, yet provides users with a 4-inch paper width capability to accommodate compressed 80-column formats. With the flexibility to provide a compressed 80-column receipt, the field worker is relieved of having to carry the bulk of a larger 80-column printer. The PW40 easily handles 120 feet of thermal paper, reducing the frequency of changing paper rolls.

A vehicle charger option ensures a long day's work in the field. With a patented sleep mode for battery conservation, the PW40 automatically activates itself when it senses data input.

The Intermec PW40 is fully compatible with the Intermec 6808, 681, 682 and 782 line of printers and is backed by a one-year warranty.

Intermec

Physical Description

The Intermec PW40 thermal workboard printer is a reliable four inch printer that offers exceptional print clarity along with the versatile capability of printing text, graphics and logos.

Physical Characteristics**Without Card Reader**

Length: 21cm (8.25")

Height: 6.7cm (2.62")

Width: 35.25cm (13.9")

Weight Empty: .95kg (2.11 lbs.)

With batteries: 1.13kg (2.51 lbs.)

With batteries and paper: 1.39kg (3.07 lbs.)

With Card Reader

Length: 21cm (8.25")

Height: 8.57cm (3.38")

Width: 35.25cm (13.9")

Weight Empty: 1kg (2.21 lbs.)

With batteries: 1.18kg (2.62 lbs.)

With batteries and paper: 1.43kg (3.16 lbs.)

Standard Features

Direct thermal line printer able to print characters, graphics and bar codes.

Power

Supply: Two internal batteries; user replaceable

Battery Type: Lithium Ion 1.8 amp/hr, 7.2v, 1350mAh

Battery Life: Print duration per charge is over 9144cm (3600")

AC Adapter/Recharging: Three hours to quick charge or nine hours to full charge, using a 12V vehicle charger with adapter or standard AC wall charger with power adapter.

Hardware

Interfaces: RS-232 serial

Print Specifications

Print Resolution: 203 dots per inch (dpi)

Print Width: 11.2cm (4.4")

Print Speed: 5.1cm (2") per second

Characters/Fonts

Three resident fonts and at least four additional standard downloaded fonts supplied. Other fonts can be purchased.

Warranty

One year warranty. Additional service packages available.

Environment

Operating Temperature: -20° to 50° C (-4° to 122° F)

Operating Temperature with Card Reader: -10° to 50° C (14° to 122° F)

Drop Survival: Withstands multiple 122cm (4') drops to concrete

Regulatory Approvals

FCC Title 47, Part 15, Subpart B, Class B; EN 55022 Class B; EN 50082-1; EN60950

Restrictions on Use

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

North America
Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions
550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies
9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

**Europe/
Middle East & Africa**
Headquarters
Sovereign House
Vastern Road
Reading RG1 8BT
United Kingdom
tel: 44.118.987.9400
fax: 44.118.987.9401

Australia
Level 7, 200 Pacific Highway
Crowns Nest, NSW 2065
Australia
tel: 61.2.9492.4400
fax: 61.2.9954.6300

Asia
Hong Kong
Unit 2602
Convention Plaza Office
Tower
1 Harbor Road
Wan Chai, Hong Kong
SAR China
tel: 852.2574.9777
fax: 852.2574.9725

Singapore
25-16 International Plaza
10 Anson Road
Singapore 079903
tel: 65.324.8391
fax: 65.324.8393

South America & Mexico
Latin America Headquarters
17921 B Skypark Circle
Irvine, California 92614
tel: 949.442.9393
fax: 949.757.1687

Intermec South America Ltda.
Rua Arandu 1544-15 andar
Edificio Itavera
Brooklin Novo 04562-031
Sao Paulo, SP
Brazil
tel: 55.11.5501.2070

Mexico
Tamulipas 141, Primero Piso
06140 Mexico, D.F.
tel: 525.55.211.1919
fax: 525.55.211.8121

Worldwide
**Fax Document
Retrieval Service**
800.755.5505
(North America Only)
tel: 650.556.8447

Internet
www.intermec.com

Sales
800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support
800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2003 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611286-01A 01/03

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.