

MS-CONNECT 210



Connectivity Solution with Ethernet

The MS-Connect 210 simplifies connectivity of Microscan readers in industrial applications. This factory floor ready wiring box features a vivid display, convenient access holes for easy wire routing, and multiple connectivity options including Ethernet protocols.

The MS-Connect 210 is the ideal Microscan reader accessory for any users seeking an easy connectivity option.

MS-Connect 210: Easy Integration

- For fast installation and easy maintenance of any Microscan scanner or imager
- IP65 rated industrial design
- Better organization of cables and wiring on factory floor
- Protocol conversion allows connection via Ethernet

Simple Connectivity Solution for:



Microscan laser barcode scanners



Microscan 2D barcode imagers

For more information on this product, visit www.microscan.com.

Ethernet Connectivity

Connect to a host using serial or Ethernet connection. Ethernet TCP/IP and EtherNet/IP protocols are available out of the box.

Informative Display

Providing two lines of decoded information, the optional display is ultra-bright and easy to read.

I/O Indicators

The front panel on the MS-Connect 210 provides visual confirmation of performance. Multiple colors are used for easy recognition.

Relay Modules

The MS-Connect 210 includes slots for optional relay modules to allow for greater use of external devices including light stacks.

Practical Design

Four access holes located on the box allow users quick, easy, and clean wiring of inputs and outputs. Mounting is simplified with four accessible through-holes for mounting screws. An optional plate is available for easy DIN rail mounting.

Clear Wiring Path

Wiring to the appropriate terminal block is easily accomplished, due to the access holes and a clear area located between the terminal rows.

Additional Power

The MS-Connect 210 includes the option to power three additional readers.

MICROSCAN®

www.microscan.com
Product Information: info@microscan.com
Technical Support: helpdesk@microscan.com