PRODUCT SPECIFICATION

STANDARD FEATURES

Dimensions: Weight 1.98 lbs (.891 kg)

Shipping Weight 3.5 lbs.

(1.58 kg)

Display: 16 character (1 line) LCD

Printing: Thermal direct with thermally

coated supplies (no ink or

ribbon required)

Print Head: 6020/6025 - 1.2"

(30 mm/224 dots)

6021/6026 - 1.5" (38 mm/224 dots)

Keypad: 12 numeric/function keys

Features Selectable at Initial Purchase:

- Bar Code Fonts (choose one)
- Human Readable Fonts (choose two)
- Date and Time Format

Black to White Print Ratio:

30% black maximum

Host System

Interface:

- RS-232 serial with 6096 cable
- XON/XOFF flow control
- 300, 600, 1200, 2400, 4800, or 9600 baud
- Printable & non-printing control characters
- ASCII transmission code

SUPPLIES

Only Monarch supplies are recommended. For high density and serial bar codes, Monarch "premium" supplies are recommended.

Supply Sizes: 6020/6025

Width - 1.2" (30 mm) Lengths - .55" (13.75 mm),

.785 (19.75 mm),

1.1" (27.5 mm), 2.2" (55 mm),

2.5" (62.5 mm)

6021/6026

Width - 1.5" (38 mm) Lengths - 1.1" (27.5 mm),

1.57" (39.25 mm), 2.5" (62.5 mm), 3.0 (76 mm)

Code 39 and MSI bar codes require synthetic (type A) supplies.

PERFORMANCE

Power: 12 VDC battery module standard with standard DC

connector

Minimum Battery Recharge Time:

- 8 hours standard wall charger
- 5 hours using the 8 station charger

Expected Duration of One Charged Handle:

1 roll of 1,000 1.1" labels

Battery 3.6 V lithuim battery maintains **Backup**: RAM (approximately 2 year

battery life)

Print Speed: 1.8" per second nomimal

Cleaning: Use the Monarch 6076™

Cleaning Kit to clean the printhead and pinch roller.

In high temperature and high humidity the printhead may need to be cleaned more often.

Product Life: Five years or 750,000 inches,

whichever occurs first.

Electrostatic Discharge and Air Quality:

Environments prone to static discharge or extreme air quality conditions may experience some problems with the printer. Monarch suggests that you take precautions to minimize these problems. Contact Monarch sales or service for recommended ways to minimize static discharge and air quality control methods.

OPTIONS

- 6076™ Cleaning Kit
- ◆ 6092[™] Battery Handler
- 6093-04 110V Wall Charger
- 6094™ 4 Station Charger
- 6096™ Communication Cable
- ◆ 6012[™] Wirestand
- PHOLO Holster

In our ongoing effort to deliver the best technology, specifications are subject to change without notice. A copy of the applicable written Monarch warranty statement is available upon request.

Monarch® Scout Peripheral Printers

PORTABLE PRINTER

THERMAL DIRECT

OPERATES WITH HANDHELD DATA COLLECTION DEVICE

FORMAT SOFTWARE CAN BE CUSTOMIZED



Monarch® PAXAR