Pertech Resources Inc.



the best cost solution in the industry today.



custom printing solutions for the banking, gaming, money order, kiosk and



Innovative design features, coupled with industryleading HP inkjet technology



Imaging solutions designed for today's needs.

Easy to Install

Easy to Run

Easy to Maintain

Easy on the Budget



Experience the INKPACT™
Evolution

5300 Series Inkjet and Impact Banking Transaction Printers with INKPACT™ Technology

Smart Design

The 5300 Series printers with versatile INKPACT™ Technology are designed with today's need for speed, versatility, compatibility and reliability in mind. Ideal for any printing application that requires customer receipts or printing on an inserted form, these printers are a cost effective solution to any banking application need.

Solid Reliability

The design is the result of years of research and experience building state of the art printers for the banking, retail and POS industries.

Packed with Features

- Standard full width independent form validation of up to 14 printed lines.
- LED's indicate modes of operation, paper present, ink conditions and printer status.
- USB 2.0 and RS232 serial interfaces standard on every printer.
- One-button setup configuration for a simple, trouble free installation.
- Semi-automatic self-loading feed mechanism simplifies paper loading and minimizes user intervention.
- Snap-in ink jet cartridges ensure fast trouble-free replenishment.
- Bi- Directional optional automatic form alignment feature.
- Microsoft certified driver

Small Footprint

Compact with dimensions kept to a minimum, Pertech's 5300 Series' functional design is highlighted with stylish, ergonomic features for the user's convenience.



Low Total Cost of Ownership

Pertech's 5300 series' total cost of ownership is the lowest of any transaction printer available on the market today. Low TCO combined with the 5300's extensive list of features delivers a cost effective teller transaction solution that is the top of its class.

Low Noise

Acoustically designed isolated print mechanism and platen solution for silent operation.

High Speed

Bidirectional logic seeking print engine provides full width printing at a speed of 5 lines per second.



Pertech 5300 Inkjet and Impact Printer Specifications

Weight R/V Models **Ext. Power Supply**

5.75 Lbs. / (2.61 kg) 1.12 Lbs. Max. / (.051 kg)

Impact: 60 Watt 24V Brick or Inkjet:15 Watt 24V Wall Mount **Power Supply** Roll Paper

Width 3.0" +/- .03" / (76mm +/- .762 mm)

3.5" Max./ (88.9 mm) Diameter

1 or 2 Ply Plies

.0064" Combined Two Ply (.1626 mm) **Thickness**

Core ID

5/8" Min. / (15.875 mm) Original + 2, 5.5" by 2.75" Min.(139.7 X 69.9mm) Form .0015 to .0047 Multi-Ply / (.0381-.1194 mm) Thickness Total Media Thickness .012" Total (Includes Receipt) / (.305 mm) Impact Ribbon

Purple 4 Million Characters Part # 100629012 Black 3 Million Characters Part # 100629011 InkJet Cartridge Part # 108541-001 (Black Ink) Interface

RS232C (DB9M)

USB 1.1, 2.0 Compatible **Baud Rates** 9600, 19200 & 57600

Input Buffer

Cash Drawer One 6 Pin Female Tele-Connector

2 Drawer Capability /Single Sense

Print Speed Ink Jet: 5.0 LPS (Lines Per Sec.)@ 40 CPL(Characters Per Line),16 CPI (Characters / Inch) and 6LPI (Lines /inch)

Impact: 4.7 LPI @ 40 CP L, 16 CPI and 6LPI

Paper Feed 5 Inches Per Second

Printhead HP Inkjet / 9 Wire Impact Dot Matrix

Line Pitch 5, 6, 7, 8, LPI

Character Sets USA

437 USA, 863 Canadian-French and 1252 Latin I Code Pages

7 x 12 @ Max. 66 CPL 5 Fonts 10x10 @ Max. 44 CPL

12 X 12 @ Max. 33 CPL OCRA (Ink Jet ONLY) Times New Roman

InkJet: 12 Nozzle / Impact: Full 9 wire **Graphics**

InkJet: 3" Wide Validation 2.5" Receipt, 96X80 DPI Draft Mode, **Print Line**

96X160 DPI Standard Mode.

Impact: 72X80 & 72X160 DPI, 2.5" Validation and Receipt

Validation Up to 14 Lines on Inserted Form at 8 LPI

Optional Bi-directional Form Auto-Alignment Feature

Compatibility Modes Seven

User Memory Flash 64K Expandable to 512 16K Expandable to 400K

Environmental

Noise 60 db impact, 49 db Inkjet

10° to 40° C, Humidity 10-90% Non-Condensing -10° to 40° C, 10-90% Non-Condensing Operating Storage

Expected Life

Printhead Impact 300 Million Impacts Per Wire

PCB 61K hrs

Mechanism 9.5 Million Printed Lines 630K Validations

Agency Listings FCC Class B, C TUV CUE Windows XP, 2000, MS Certified Vista Drivers

Utilities Logo Dowload - Configuration

Available models

5351- Receipt / Validation 5354- Validation Only

Impact

5371- Independent Feed 5374- Validation Only



Pertech Resources Inc.. 860 College View Drive Riverton, WY 82501 800-800-6614

For additional information about Pertech® products contact us at the address below or visit our

www.pertechresources.com

Copyright© 2009 Pertech Resources, Inc. All Rights Reserved. Patents pending. All trademarks or registered trademarks are the property of their respective owners. Printed in U.S.A. Product specifications are subject to change.

Dimensions

Height

5.353 / (140.46 mm) Width

7.1" / (180.34 mm)

Length

8.93" / (226.82 mm)



