

Falcon® 4210

Windows® CE PDA Data Collector



Ideal For:

- Retail Store Management
- Line Busting
- Inventory Control
- Logistics
- Field Service

Features:

- Compact/weights under 12.9 oz / 365 grams
- Laser and Mag Stripe input
- Windows® CE 3.0 Operating System
- WiFi compatible (802.11b) RF providing Real-Time communications
- Numeric keypad for ease of data entry
- Microsoft® Pocket Applications included

Flexible Mobile Computing Featuring Windows® CE

The new Falcon® 4210 is a compact, rugged handheld computer combining the flexibility of Microsoft's® Windows® CE operating system and applications with RF data communications, bar code scanning and optional magnetic stripe card processing. The Falcon® 4210 is designed for retail, logistics, and field service applications where maximum performance is required in a compact form factor.

Features Users Demand

The Falcon® 4210 incorporates all the top features users are demanding today. Laser, Magnetic Stripe Input, and large 1/4 VGA touch screen display. A user accessible PC Card slot allows easy expansion for additional memory, modem, or RF communications. A built-in 16 key numeric keypad provides additional ease of data entry. Tested to repeated 4.0' / 1.2m drops to concrete, the Falcon® 4210 is designed to handle demanding data collection tasks.

Ready to Run

The Falcon® 4210 includes Microsoft® Pocket Word, Pocket Internet Explorer (browser), and Inbox (email) applications so you are ready to run right out of the box. Application development is a snap with Windows® CE as many 3rd party development tools are available for both batch and RF environments. Additionally, PSC offers a variety of development tools for the Falcon® 4210 including RFBUILDER, and our PowerNet terminal emulation solution for VT100, VT220, HP700/92, IBM 3270, and IBM 5250 emulations.

Batch and Wireless Models

For both local and remote data collection applications, the Falcon® 4210 Batch portable is an ideal solution. Data can be sent to a host using standard RS232 communications using the docking cradle or a direct connect cable. An optional integrated modem kit is available for dial-up communications supporting speeds up to 56Kbps. The Falcon® 4210 RF portable sets the standard for flexibility when it comes to wireless communications, providing connectivity for data collection applications where real-time information is critical. The Falcon® 4210 is available with the leading 802.11b radios including Cisco Aironet, Lucent (Agere) Orinoco, and Symbol S24 HR providing interoperability with other leading WiFi compliant radios.



Specifications

Falcon® 4210

These product Specifications are subject to change without notice. Additional information concerning this product or other PSC products and services can be found at the PSC website or contact your PSC representative for more information

Mechanical

Dimensions

Length: 6.85" / 174 cm

Width: 3.35" / 8.5 cm

Depth: 1.57" / 4.0 cm

Weight (w/battery pack): 12.87 oz. / 365 g

Display

FTN panel, grayscale LCD, EL Backlit

240 (W) x 320 (L) pixels

Keypad

16 physical keys including numeric, TAB, ESC, FUNC, brightness and contrast controls

Environmental

IP rating: IP 42

Temperature rating

Operating: 32° to 122° F / 0° to 50° C

Storage: -4° to 158° F / -20° to 70° C

Humidity: 5 to 95% RH non-condensing

Shock: Withstands multiple 4.0' / 1.2m drops to concrete

Communication

RS232C: Full duplex asynchronous communication; up to 115,200 baud rate

Infrared: IrDA 1.2 (SIR) compliant; up to 115,200 baud rate

PCMCIA: Type II slot accepts memory, modem, and RF cards

Optical

Light source: Visible Laser Diode (VLD) 650 nm

Scan rate: 39 ±3 scans/sec. (1D Laser)

Depth-of-Field: See chart below

Decoding Capability

1D Laser:

UPC A, E / EAN 8, 13

Code 128

Interleaved 2 of 5

Code 39

Code 11

Codabar

Delta

EAN 128

Code 93

Standard 2 of 5

Code 39 Full ASCII

Code 32

MSI / Plessey

Toshiba

Safety and Regulatory

Electrical: Complies to CE

Emissions: FCC Part 15 - Class A, VCCI-A,

EN 55022-A, EN 55024

Laser classification: CDRH Class II;



(CAUTION: Laser Radiation – do not stare into beam); IEC 60825 Class 2

System

Operating System

Microsoft® Windows® CE 3.0

CPU

MIPS core RISC CPU, 32 bits, 92 MHz, built in real-time clock

Memory

FlashROM: 32 MB for OS and applications

SDRAM: 32 MB for data

Buzzer

Piezoelectric buzzer, software controlled

LED Indicator

Dual color (green/red) good read indicator for scanner or MSR

Power Options

9VDC external adapter, 2 Amps

Lilon Pack 1550 mAh

Power Consumption (Lilon battery @ 4V)

Standby: 85 mA

Suspend: 31 mA

Battery Charge

3 hours with external adapter, 2.5 hours with docking station

Input Devices

Touch screen, stylus, numeric keypad, full alphanumeric software keyboard, mag stripe reader (3 track) and bar code scanner

Docking Station

Interface: RS232

Charging: Quick charge; 2.5 hours

Power input: Regulated AC adapter; 9 VDC @ 2 Amps

Depth-of-Field Chart

(printing resolution, contrast and ambient light dependent)

Label Density	Standard 1D Laser Typical Range			
5 mil	2.0"	to	5.2"	/ 5.1 to 13.2 cm
PDF / 6.5 mil				
7.5 mil	1.7"	to	8.0"	/ 4.3 to 20.3 cm
10 mil	1.8"	to	10.0"	/ 4.6 to 25.4 cm
100% UPC	1.9"	to	13.0"	/ 4.8 to 33.0 cm
PDF / 15 mil				
20 mil	*	to	20.0"	/ * to 50.8 cm
40 mil	*	to	25.0"	/ * to 63.5 cm
55 mil	*	to	30.0"	/ * to 76.2 cm

* Minimum distance determined by symbol length & scan length



Falcon® 4210 Docking Station

PSC Inc.

959 Terry Street

Eugene, OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140



PSC Worldwide Sales and Service locations

Australia - NSW

Tel: 61 2 9878 8999

Fax: 61 2 9878 8688

Belgium

Tel: 32 2 414 74 09

Fax: 32 2 410 11 63

Brazil

Tel: 55 11 5507 7721

Fax: 55 11 5507 7696

Chile

Tel: 562-339-7000

Fax: 562-339-7985

China

Tel: 86 10 6857 9048

Fax: 86 10 6857 8699

France

Tel: 33 1 64 86 71 00

Fax: 33 1 64 46 72 44

Germany

Tel: 49 6151 93580

Fax: 49 6151 935897

Hong Kong

Tel: 852 25846210

Fax: 852 25210291

India

Tel: 91 11 24621586

Fax: 91 11 24641662

Italy

Tel: 39 039 629031

Fax: 39 039 6859496

Japan

Tel: 81 3 3491 6761

Fax: 81 3 3491 6656

Latin America

Tel: 1 305 539 0111

Fax: 1 305 539 0206

Singapore

Tel: 65 6435 1311

Fax: 65 6226 1242

Spain

Tel: 34 91 746 28 60

Fax: 34 91 742 35 33

Sweden

Tel: 46 4010 84 92

Fax: 46 4010 84 91

United Kingdom

Tel: 44 1923 809500

Fax: 44 1923 809505