

Sensormatic® PowerPad® Pro Ultra•Max® Label Deactivator



Description

The PowerPad Pro is a ScanMax™ distance deactivator providing superb deactivation reliability, impressive throughput speed, and an optional magnetic media safe mode to safeguard pre-recorded video and audio cassettes.

The PowerPad Pro can be mounted in a variety of ways including on the counter, below counter, flush with the counter or on a bracket at the edge of the counter.

PowerPad Pro deactivates labels up to 17.5 cm (7 in.) above the surface of the pad at a throughput speed of up to 200 cm/sec. (80 in./sec.).

Features

- **Performance.** The PowerPad Pro's deactivation height allows deactivation of both source tagged and retailer tagged merchandise.
- **Magnetic media safe.** A magnetic media safe mode at reduced height safeguards pre-recorded audio and videocassettes.
- **Integrated audible and visual notification.** Label deactivation notification is built into the PowerPad Pro. A remote module with a key switch also can provide visual and audible confirmation of label deactivation.

Specifications

Power

100-120 / 200-240 Vac; 1A @ 50-60Hz

Power Consumption

Typical: 10W @ 120V, 15W @ 240V

Max: 50W @ 120V and 240V

Operating Frequency

58 kHz (±200 Hz)

Operating Temperature

0° to 40° C (32° - 104° F)

PowerPad Dimensions

LxWxD: 39.4 x 17 x 5.6 cm
(15.5 x 6.75 x 2.2 in.)

Weight: 9.6 kg (21 lbs.)

Cable: 2.9 m (9.7 ft.)

Controller Dimensions

HxWxD: 10.1 x 26.2 x 22 cm
(4.0 x 10.3 x 8.7 in.)

Weight: 2.5 kg (5.5 lbs.)

Controller Emissions

47 CFR, Part 15

ENS 300 330

EN 301489

EN61000-3-2

EN61000-3-3

Controller Safety

UL60950

CSA C22.2 No. 60 950

EN 60 950

tyco
Safety
Products

ELECTRONIC ARTICLE SURVEILLANCE



The PowerPad Pro is available as a table top, under-the-counter or end-of-the-counter deactivator.



The compact ScanMax Pro Controller features table-top, vertical, and under-the-counter mounting options.

Remote module




The remote module can be mounted almost anywhere on the checkstand for visual and audible notification of deactivation. The module features a key switch for turning the deactivator on or off.

The PowerPad Pro will deactivate Ultra•Strip® II and Ultra•Strip III labels. Place labels within 8.9 cm (3.5 in.) of the bar code for optimal deactivation performance and convenience.



Ultra•Strip III



Ultra•Strip II

ScanMax Pro Controller


The ScanMax Pro Controller provides the power and operating capabilities to the deactivator antenna. It is compatible with all ScanMax Pro deactivator antennas. Its features include:

- Deactivates up to two labels per second.
- Small size requires minimal space.
- Optional mounting bracket for under-the-counter or sidewall installation.
- Automatically detects antenna type and remote module.
- Simple button press to select deactivation mode and label type.
- Auto phasing capability.
- Separate communications ports for POS and service.

For further details on all ScanMax Pro products, refer to the ScanMax Pro Deactivator Systems Planning Guide 8200-0054-02.

Deactivator mounting options

Flush mount, end-of-the-counter flip-down tray, and under-the-counter mounting.



End-of-counter brackets

Product Codes

- ZBSMP-PW..... System, including deactivator, controller, remote alarm module, power cord
- ZESMPRO Controller with cord
- ZBSMPRO Controller only
- ZBSMPPP Deactivator only
- ZBSTP-PP-B1 ... Flush mount tray
- ZBSTP-PP-B2 ... Under-the-counter bracket
- ZBSTP-PP-B3 ... Cantilever mounting bracket
- ZBSTP-PP-B4 ... Flip Mount bracket

tyco
Safety
Products