



TR 220™

**Integrated, Scan-and-Print
Mobile Printer**

Scan AND print on the go with one easy-to-use mobile printer!

For users of the Symbol® SPT 1700/1800 or PPT 2700/2800 handheld devices, the ergonomically designed TR 220 is Zebra's rugged new solution for one-handed scanning and printing in the aisles or on the route!

Maximum Mobility and Convenience

A two-inch printer that locks together securely with a terminal, the TR 220 is powered by a Li-on battery and can print up to 2,500 inches on a single charge. Its direct connection enables this space saver to cost-effectively eliminate printer cables or radios. Plus it can print labels (including linerless), receipts, and tags, making the lightweight TR 220 ideal for a number of applications including retail shelf labeling, warehouse receiving and stock picking, transportation receipt and ticket printing, and healthcare specimen labeling.

The TR 220 is ideal for a wide range of applications including:

- Shelf/Bin marking
- Product identification
- Specimen labeling
- Receipt/Coupon printing
- Receiving
- Stock Picking
- Ticketing
- Inventory/Asset management



Connect with it. Count on it.™

TR 220™



Zebra's TR 220 is a great fit for pick applications since it can accommodate a high scan volume.

MAXIMUM PRINT AREA

Width: 1.89"/48mm
Length (with standard memory):
11"/279mm

RESOLUTION

203dpi/8dots per mm

MAXIMUM PRINT SPEED

2"/51mm per second

MEMORY

Standard: 512KB Flash; 128KB SRAM

PHYSICAL CHARACTERISTICS

Width: 4"/102mm
Length: 9.6"/244mm
(not including Symbol PDT)
Height: 7.7"/195mm
Weight: 1.3lbs/.59kg
Shipping Weight: 2.15lbs/.98kg

MEDIA SPECIFICATIONS

Label and liner width: 1"/25.4mm to
2.25"/57.15mm

Specifications at a Glance*

STANDARD FEATURES

Print Method: Direct thermal
Construction: Tough polycarbonate plastic alloy
512KB Flash memory; 128KB SRAM
Lithium Ion battery
Easy loading label path
Connection with Symbol SPT 1700/1800 and
PPT 2700/2800 PDTs (not compatible with SPT
2800 Color/GSM & Corona 2D scanner)
Patented locking system
Trigger-activated scanning
Black mark, gap and notch sensing
Programming Language
ASCII EPL2 programming language (Page Mode)
Text and bar codes printed in 0°, 90°, 180°, 270°
Variable field support (up to 100)
Counter support (up to 10)
Variable field addition and subtraction
Status reporting
Form, font and graphics storage
Line mode support

OPERATING CHARACTERISTICS

Environment

Operating Temp. 40°F/5°C to 105°F/40°C
Storage/Transport Environ. -40°F/-40°C to
140°F/60°C
Operating Humidity 10–80% non-condensing
Storage Humidity 10–90% non-condensing

Electrical

7.5V Lithium Ion battery
External Charger options

Communication Interface Capabilities

Serial interface to Symbol PDTs (SPT 1700/1800
& PPT 2700/2800)

Agency Approvals

FCC (Part 15 Subpart C and CE requirements);
meets UL, CUL and CB scheme requirements

MEDIA CHARACTERISTICS

For optimum print quality and printer perform-
ance, use Genuine Zebra supplies.

Labels

Maximum roll size: 2"/50.8mm O.D. on a
1"/25.4mm I.D. core
Thickness (label & liner):
.0025"/.064mm–.007"/.18mm
Media type: Roll-fed, die-cut, continuous labels,
continuous receipt paper, tag, linerless media
with optional linerless platen

FONTS/GRAPHICS/SYMBOLS

Fonts and Character Sets

Standard Fonts: 5 resident fonts expandable 8x
Standard international character sets
(Asian characters optional)
Soft font storage in flash memory

Graphic Features

Graphics, line and box drawing features; PCX
bitmap supported

Bar Code Symbolologies

Linear Bar Codes: Code 39; Code 93; Code 128A,
B & C; Codabar; Interleaved 2 of 5; Postnet;
UPC-A, 2 & 5 digit add-on; UPC-E, 2 & 5 digit
add-on; EAN 8, 2 & 5 digit add-on; EAN 13, 2 & 5
digit add-on; UCC/EAN-128; German Postcode
2-Dimensional: PDF-417 (Macro PDF-417), QR
Code (Japanese font only)

OPTIONS AND ACCESSORIES

Linerless printing with optional linerless platen
(factory installed only)
Asian font capability (factory installed only)
Spare Lithium Ion battery packs
UBC battery charger
Nylon holster

*Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved.



HEADQUARTERS

ADDRESS: 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A.
PHONE: +1 847.634.6700 or +1 800.423.0442 FAX: +1 847.913.8766
WEB: www.zebra.com

OTHER LOCATIONS

USA: California, Florida, Rhode Island, Wisconsin EUROPE: France, Germany, Italy, United Kingdom
ASIA-PACIFIC: Australia, China, Japan, Singapore, South Korea



An ISO 9001 registered company
©2002 ZIH Corp.
Printed in U.S.A.
#13047L, (7/02), 5M